

Uncertainty analysis for measuring greenhouse gas emissions in the building construction phase: a case study in China

Jingke Hong ^a, Geoffrey Qiping Shen ^{a, **}, Yi Peng ^{b, *}, Yong Feng ^a, Chao Mao ^c

^a Department of Building and Real Estate, Hong Kong Polytechnic University, Hung Hom,
Kowloon, Hong Kong

^b School of Public Administration, Zhejiang University of Finance & Economics, Hangzhou,
PR China

^c Faculty of Construction Management and Real Estate, Chongqing University, Chongqing,
China

Abstract

Uncertainty analysis is useful in determining whether the results of life cycle assessment are sufficiently reliable and valid when making optimal decisions. However, only a few studies have measured carbon emissions by considering the inherent uncertainty during building construction phase that may result in the misinterpretation of critical parameters. To address such weakness, a multi-method-based uncertainty analysis framework was developed in view of the basic characteristics of the construction practice. This framework integrated the deterministic and probabilistic approaches to facilitate the uncertainty assessment in quantifying carbon emissions and to provide insights into the sensitive construction activities from the uncertainty perspective. The developed framework was examined through a mix-use project in Guangzhou China. Results showed that the uncertainties in the measurement method and geographic representativeness are the major uncertainty sources for the building construction phase. The total greenhouse gas emission for the target building was 8791.5 tonnes of carbon dioxide equivalent with a 9.8% coefficient of variation, which was in line with the result calculated by the deterministic method and with the result extrapolated based on the data collected from China. The results of the scenario analysis showed that the proportion of 1% in contribution analysis and the coefficient of variation of 18% in uncertainty analysis can be regarded as the baseline for determining the critical input parameters. This study lends a useful tool for monitoring the uncertainty of LCA studies in the construction practice. In addition, this framework can facilitate to avoid the misinterpretation of the final results during the decision-making process. Although this study focuses on Chinese construction industry, it also provides good

references for measuring uncertainty of greenhouse gas emissions of construction industries around the world.

1. Introduction

The carbon dioxide (CO₂) emissions related to the residential and commercial building sector have been a global concern. As the primary contributor of global greenhouse gas (GHG) emissions, the construction industry plays a significant role in global warming. The Intergovernmental Panel on Climate Change asserts that the building sector contributed 40% to the total energy consumption and 25% to the global total CO₂ emissions (IEA, 2007; Metz et al., 2007). In China, the situation is significantly urgent owing to its accelerated urbanization. According to the 12th Five-Year Plan, the urbanization rate in China will reach a historic high of 51.5% in 2015. As the result of such extensive construction, the growth rate of energy consumption in buildings is more than 10% in past decades (Chang et al., 2014), producing large amount of CO₂ emissions. Therefore, the negative effects of extensive building constructions on China's environmental sustainability should be evaluated. In fact, the carbon emissions generated from building construction activities have been extensively studied in China. At the national level, the GHG emissions from the construction sector have been quantified using a series of macro-level analysis techniques, such as input-output (IoO) analysis and structural path analysis (Chang et al., 2014; Chen and Zhang, 2010; Liu et al., 2012). At the project level, numerous studies have investigated the carbon emissions from different types of buildings. As the major building type, residential buildings play a significant role in GHG emissions. Gao (2012) measured the embodied carbon footprint of residential buildings by conducting an empirical study of 17 buildings in Jiangsu province. Liu et al. (2009) quantified the life cycle CO₂ emissions of residential communities in China. Regarding office buildings, Wang et al. (2016) employed two case studies to illustrate the current GHG emission reduction performance of Chinese green buildings. Yao (2013)

developed a benchmark for the carbon emissions from office buildings based on life cycle assessment theory. The current research hotspot for GHG emission quantification lies in investigating the influence of innovative construction techniques such as precast construction (Aye et al., 2012; Mao et al., 2013). In sum, previous research provides relevant insights into the current GHG emission status of the construction sector from the industrial and project perspectives. Nonetheless, the uncertainties generated during modeling are yet to be extensively looked into.

As an effective tool in the decision-making process for saving energy and reducing emissions, life cycle assessment (LCA) is widely used in the construction industry for environmental quantification. Theoretically, the outcome of an LCA analysis should be reliable and valid for decision makers to make optimal decisions. However, in the construction practice, the uncertainty of the inherent data affects the accuracy of LCA results. As such, the importance of uncertainty analysis behind the LCA results has been emphasized in recent years (Ciroth et al., 2002; Geisler et al., 2005; Sonnemann et al., 2003; Sugiyama et al., 2005). Therefore, the present study establishes a multi-method-based analytical framework to simulate the uncertainty that emanates from the computational process in the construction industry. This study aims to accurately assess the GHG emissions from buildings and to contribute to the literature from three aspects. First, this paper develops a multi-method-based analytical framework that can systematically identify the uncertainty sources and that can quantify the uncertainty bundled in construction activities. This framework can reinforce the importance of measuring uncertainties in LCA studies and can avoid the misinterpretation of the final results during the decision-making process. Second, the integration of qualitative and quantitative assessment methods provides a possible solution for assessing the uncertainty of LCA studies

in the construction practice. This method also provides a sufficient understanding on the uncertainty related to building construction. Third, this paper identifies the critical parameters that influence the GHG emissions during building construction in the context of China.

The remainder of this paper is organized into six sections. Following the Introduction, Section 2 presents an overview of the recent uncertainty analysis in LCA studies. Section 3 establishes a multi-method-based uncertainty analytical framework by considering the basic characteristics of building construction. To overcome the data gap in traditional construction projects, this study collected input data based on an extended system boundary, considering onsite miscellaneous works and construction-related human activities. The focus was directed toward data inaccuracy analysis rather than the lack of data. The study mainly focused on the parameter uncertainty given that it is most sensitive to the final result. Section 4 applies the uncertainty analysis framework for measuring GHG emissions to a real building case. Section 5 discusses the proposed approach along with policy implications, and Section 6 presents the conclusions.

2. Overview of uncertainty analysis in LCA studies

Various researchers have investigated the sources of uncertainty based on LCA analysis. Weidema and Wesnæs identified five indicators, including data reliability, completeness, temporal correlation, geographical correlation, and technological correlation, to evaluate the additional uncertainty caused by data availability and quality (Weidema, 1998; Weidema and Wesnæs, 1996). Huijbregts et al. (2001) classified these indicators into two groups, namely, data inaccuracy and lack of data. With the development of LCA methodology, recent studies have determined that uncertainty not only comes from input parameters but also from the initial assumptions and the selected methodology. Geisler et al. (2004) identified uncertainty sources

according to the different phases of LCA. These researchers regarded the measurements of elementary flows, temporal and spatial correlations, and production process as the uncertainty sources in life cycle inventory analysis (LCIA) phases. [Huijbregts et al. \(2003\)](#) emphasized that in addition to the uncertainties from input data, LCA outcomes can also be influenced by selected scenarios and mathematical models. [Basset-Mens et al. \(2004\)](#) quantified uncertainty by considering the variability in the LCA in pig farming systems. The uncertainty sources included technical performance, emission factors, and the functional unit. After reviewing 24 LCA studies focusing on quantitative uncertainty analysis, [Lloyd and Ries \(2007\)](#) concluded that uncertainty and variability come from three LCA modeling components, namely, input data, normative choice, and model, whereas [Cellura et al. \(2011\)](#) categorized the uncertainty sources in LCA analysis as methodological choices, initial assumptions, and quality of data. [Williams et al. \(2009\)](#) divided uncertainty types into data, cutoff, aggregation, temporal, and geographic uncertainty to conduct uncertainty analysis for a hybrid LCA model. [Gavankar et al. \(2015\)](#) focused on the communication of uncertainty in LCAs than on the technical aspects and summarized five criteria to facilitate uncertainty communication. In sum, previous works addressed three different uncertainty sources significant in LCA-related studies. These sources are parameter, model, and scenario uncertainties in which the parameter uncertainty is the most sensitive to the final LCA outcome ([Huijbregts et al., 2003](#)).

Assessment tools vary in terms of uncertainty types, and they can generally be divided into qualitative and quantitative approaches. The data quality index (DQI) is the most commonly used qualitative assessment method because of its high applicability and feasibility. The data quality evaluation matrix ([Weidema, 1998](#)) and the transformation matrix ([Kennedy et al., 1996](#)) are the two most efficient tools used in DQI assessment. However, DQI remains limited in terms of its assessment accuracy due to the subjective determination of data quality.

Although the quantitative analysis techniques are complemented for the current qualitative uncertainty assessment methods to minimize variations, the results still tend to be underestimated as specified by [Coulon et al. \(1997\)](#). Considering the aforementioned limitations in the application of qualitative approaches in uncertainty analysis, quantitative approaches have been introduced based on data availability. [Basson and Petrie \(2004\)](#) adopted a set of statistical methods to differentiate and identify both the technical and valuation uncertainties in the LCA analysis of a coal-based power station. [Canter et al. \(2002\)](#) conducted uncertainty analysis in LCA for four beverage delivery systems. The group applied DQI to evaluate the uncertainty of target input data, which were first selected according to their individual contributions, and used Monte Carlo simulation (MCS) to obtain the overall uncertainty and model variance. [May and Brennan \(2003\)](#) performed uncertainty analysis by implementing three steps: gravity analysis to determine data contribution, uncertainty analysis, and sensitivity analysis. [Imbeault-Tetreault et al. \(2013\)](#) outlined an analytical approach for uncertainty analysis to mitigate the resource intensity in MCS and validated this quantitative method in a real case to reveal its importance in uncertainty calculation. [Herrmann et al. \(2014\)](#) established an LCA classification matrix to summarize the inherent uncertainty scale under each LCA model; this matrix provided an index map for LCA analysts and decision makers. In general, fuzzy logic analysis, interval theory, and possibility uncertainty analysis are commonly used for LCA uncertainty evaluation given that the data are insufficient for further processing ([Chevalier and Le Teno, 1996](#); [Tan et al., 2002, 2007](#)). By contrast, stochastic methods such as MCS can be adopted if a large amount of actual data can be observed and collected ([Geisler et al., 2004](#); [Lo et al., 2005](#); [Venkatesh et al., 2010](#)). In particular, stochastic methods are superior to other methods due to their inherent advantages in capturing the variability and uncertainty in LCA. [Tan et al. \(2002\)](#) applied

possibility theory to assess the uncertainties in LCIA and clarified that possibilistic methods have advantages in computational efficiency when compared with probabilistic approaches. [Andre and Lopes \(2012\)](#) held the same view by comparing possibilistic and probabilistic approaches and identified that the latter is limited by a relatively slow computational process but can provide sufficient uncertainty information. [Lloyd and Ries \(2007\)](#) asserted that stochastic methods were mostly used (67%) in previous research, followed by scenario analysis (29%) and fuzzy data sets (17%). This study summarizes the typical uncertainty sources and their corresponding assessment methods as shown in [Table 1](#).

The estimation of uncertainty in LCA analysis is not only associated with uncertainty sources and assessment methods, but also with the research scope and objectives. Given that this study aims to establish an uncertainty analysis framework for LCA in building construction, it considers some basic characteristics relevant to the construction industry, especially for building construction. First, a specific building is distinctive due to its characterized building profile such as design parameters and construction structure. Therefore, elementary flows may vary among different buildings. This specificity determines that all input parameters involved in a certain building are unique. In this case, sufficient data can hardly be collected to describe the probability distribution of the elementary flows of buildings. However, such procedure can be partially mitigated by improving the data collection quality and by enhancing the measurement method during the building construction phase. Second, unlike the manufacturing industry that is characterized by reproducibility and mass production, the inventory data of environmental emission, energy input, and resource use during building construction are rarely reported from private and public sources. The probable reason behind this condition is the confidentiality requirement

between the client and the contractor. This case verifies that the uncertainty analysis in LCA is insufficiently applied to real building cases in the construction industry.

This study aims to explore how the uncertainty analysis in LCA can be conducted and how a multi-method-based analytical framework can be established for the construction industry. This study also intends to reveal the uncertainty sources bundled in construction activities and the key parameters involved in construction processes in the context of China.

3. Research methods

Parameter uncertainties stem from the lack of knowledge about the true value of a parameter (Huijbregts et al., 2003). A probabilistic approach can be used to reflect the most probable value of the objective. Traditionally, the goodness of fit between data samples and probability distributions can be examined to identify the most appropriate probability distribution for parameters based on a certain number of observations. However, the basic features of building products result in a limited amount of actual data. In this case, expert judgment is used as a substitute for the lack of knowledge to estimate uncertainty ranges. In this case, DQI should be used as the supplement for uncertainty evaluation. However, pure DQI method has weakness in subjective evaluation, but the latest improvements in uncertainty analysis can facilitate the comprehensive assessment of the parameter uncertainty. Therefore, both DQI and probabilistic method are used in this study to address the lack of actual data in the construction industry. The data categorization system first introduced by Heijungs (1996) is used to identify the key parameters according to their uncertainty and contribution in the final output. The important parameters with high uncertainty and contribution are then selected for further analysis in the context of the construction industry.

3.1. DQI assessment method

DQI is a semi-quantitative method comprising a series of indicators that aim to describe the parameter uncertainty from different aspects. The DQI system is established based on experts' subjective judgment as well as on objective mathematical calculations. Given the characteristic of building construction, the data quality is mainly influenced by three aspects. First, the accuracy and validity of the available data is determined by the data measurement method. A consistent measurement of material flows in the construction site can improve data precision and avoid the possibility of uncertainty. However, regular investigation and subjective evaluation are frequently adopted in the construction industry owing to the restrictions in the data measurement technology. Second, the computational framework in

Table 1

Typical uncertainty sources and their corresponding assessment methods.

Uncertainty sources	Typical uncertainties	Assessment method
Assumption	System boundary	Scenarios analysis
	Functional unit	
	Allocation method	
Parameter	Material flow	DQI
	Energy flow	Fuzzy theory
	Other input data	Analytical uncertainty
		propagation
		Bayesian statistics
		Possibilistic approach
		Probabilistic approach

Model	Transformation factor Modeling	Probabilistic approach
	process of the product system	Sensitive analysis

LCA analysis implies that the calculated results may vary due to the changes in geographic climate, manufacturing technology, and data age. Third, the data sources in the construction practice are complicated because of its multitude of activities and long-term duration. Therefore, a priority system should be established to reflect the reliability by ranking different data sources. Comprehensively considering the conclusions of previous research ([Wang and Shen, 2013](#); [Weidema and Wesnæs, 1996](#)), five types of data quality indicators are identified in this study, namely, data measurement method, source of data, geographic representativeness, technical representativeness, and temporal representativeness. The score for each indicator ranges from one to five. The value represents the uncertainty of each category from low to high. In consideration of the basic characteristics of the construction industry, a DQI matrix was established (see [Table 2](#)) by [Weidema and Wesnæs \(1996\)](#) and [Wang and Shen \(2013\)](#). [Table 3](#) shows the difference of data sources from the general situation and building construction.

3.2. Contribution analysis

This section determines the contribution of each construction activity to the final cumulative results. The use of original processbased inventory data enables the calculation of the deterministic contributions for each construction activity. However, the result of the deterministic analysis is relatively imprecise because the uncertainty of all coefficients contributes to the overall uncertainty value. Such deterministic contribution can be regarded as the basic reference and cornerstone for identifying the important parameters, which

substantially contribute to the final output. [Maurice et al. \(2000\)](#) emphasized that the percentage of data contributions may vary from one model to another. Therefore, the scenario analysis is conducted to verify and validate the reliability of the selected key parameters.

3.3. MCS

MCS is a numerical method used to sample a probability distribution for the concerned factors to produce thousands of possible outcomes. The results of MCS are further analyzed to obtain the probabilities of different occurring outcomes ([Xu, 1985; Shen et al., 2011](#)). MCS is a useful tool for measuring the total uncertainty aggregated by various uncertainty factors with non-linear relationship. In this study, the total carbon emission is the aggregation of carbon emission in various activities in the construction phase. If the carbon emission in each activity is taken as a stochastic factor considering the uncertainty of parameters, then the total carbon emission should also be a stochastic factor. The statistical features of the total carbon emission can be determined through its probability distribution obtained by MCS. MCS first determines the corresponding probability distribution for each input factor. The probability distribution for the concerned factor can be obtained either by fitting a large number of existing data or by experts view. Based on the established relationship between the observed and input factors, MCS can be run with Crystal Ball software to obtain the probability distribution of the observed factor. To identify the extent in which uncertainty can be considered, the coefficient of variation (CV) is used to describe the degree of uncertainty based on the MCS results. Considering the constraints and deficiencies of data availability in the construction industry, b distribution is assumed to describe the possible value for each construction activity. [Canter et al. \(2002\)](#) and [Wang and Shen \(2013\)](#) thoroughly explored the reasons and rationale for applying Beta function in uncertainty analysis. [Kennedy et al. \(1996\)](#) established a transformation matrix to

define four unknown parameters involved in b distribution, namely, a, b, lower point, and upper point. MCS is conducted in Crystal Ball software with 10,000 iterations. The number of iterations directly determines the stability of the final

	Measurement method	Data source	Geographic factor	Technical factor	Temporal factor
5	Consistently measured data	Verified data from independent source	Field survey/measure data	Data from process studied of the enterprise with same technology	Less than 3 years
4	Regularly measured data	Verified data from interested party	Data from an area with similar production condition	Data from process studied of the enterprise with similar technology	Less than 6 years
3	Data estimated based on measurements	Unverified data from independent source	Regional data	Data from enterprises with different technology	Less than 10 years

2	Data estimated partly based on assumptions	Unverified data from irrelevant enterprise	National data	Data from process related of enterprises with similar technology	Less than 15 years
1	Subjective estimated data	Unverified data from interested party	International data	Data from process related of enterprises with different technology	More than 15 years or unknown

Table 2

Data Quality Index (DQI) evaluation system.

output. The result will be convergent with the increasing numbers of simulations, and the excessive iterations are regarded as a less efficient means to run MCS. Therefore, the examination of convergence is a valid method to confirm the appropriate number of iterations (Cowles and Carlin, 1996; Shen et al., 2011). Numerous mean values and standard deviations derived from simulations with different iterations are then generated to examine the trend of convergence.

3.4. Parameter categorization system

The parameter categorization coordinate comprehensively reflects the importance of input parameters in the dimension of uncertainty and contribution. With the CV and the percentage

Quality score Data quality indicators

of contribution represented in the horizontal and vertical axes, respectively, all coordinates can be classified into four quadrants according to the degree of their importance. These quadrants are divided into highly concerned data in the upper right part, concerned data in the upper left and lower right parts, and general data in the lower left part. The parameters in

the upper right quadrant have high percentage in contribution and uncertainty, critical to the accuracy of the accumulative results and therefore require detailed analysis.

3.5. Basic procedure of uncertainty analysis

[Fig. 1](#) shows the fundamental procedure of parameter uncertainty analysis. Contribution analysis and DQI assessment can be conducted simultaneously to determine the importance of input data based on the compilation of the original inventory. Parameter categorization, combined with scenario analysis, further verifies the critical input parameters with particular concerns. Finally, according to the assumed probability distribution for each construction activity, the overall CV and the final cumulative results are calculated with MCS.

4. Case study

The case project refers to the study by [Hong et al. \(2015\)](#), who examined a residential complex with a reinforced concrete framework in Guangdong Province, China. The gross floor area investigated in this study is 11,508 m² that comprises a clubhouse and retail outlets. The construction period was more than two years from April 1, 2008 to August 31, 2010. The system boundary covers the carbon impacts of all involved construction activities, which can be summarized in the following six categories:

Fuels used by construction equipment (Direct emissions) Electricity consumption
(Direct and indirect emissions)

Table 3

Different data source in the construction industry.

Quality score	General data source	Specific in construction industry
5	Verified data from independent source	Accounting receipt
4	Verified data from interested party	Stakeholder's report
3	Unverified data from independent source	Bill of quantity
2	Unverified data from irrelevant enterprise	Material use application record
1	Unverified data from interested party	Secondary data from the procurement agency

Onsite assembly and miscellaneous works (Direct emissions)

Building material production (Indirect emissions)

Transportation (Direct and indirect emissions)

Construction-related human activities (Direct and indirect emissions)

All data collected in this study are based on field survey and face-to-face interview with clients, contractors, prefabrication suppliers, and other stakeholders involved in the target project. The detailed process data are collected from multiple sources, including accounting receipt, stakeholder's report, bill of quantity, material use application record, and secondary data from the procurement agencies. The deterministic GHG emissions are quantified based on ISO 14064-1:2006 (ISO, 2006) used as the reference for contribution evaluation.

During the CO₂ emission quantification, 122 construction activities are involved in the emission factor collection and have been subjected to DQI analysis (see Table 4). The analysis result shows that the DQI scores vary among different construction activities. The emission factors are uncertain in terms of the measurement method, geographic representativeness, and technical representativeness. This condition may have arisen from the fact that this study engaged proxy data available on the international LCA software Ecoinvent v2.0 database. Most of these data were developed for Switzerland and Europe, and a few were established for global use. By contrast, the elementary flow data in the entire project are decomposed into 331 construction activities. Table 5 demonstrates the result of the DQI analysis. The construction inventory data have




Fig. 1. A multi-method based uncertainty analysis framework.

Original data inventory

weaknesses in measurement method and data source mainly because most material flow data are collected based on the bill of quantity, which is compiled under various assumptions. In addition, given that the major data collection method used in this study is field survey and face-to-face interview, the indicator of the temporal correlation represents less uncertainty.

5. Results

[Table 6](#) illustrates the ranking list of the construction activities in terms of their contribution and uncertainty.

As two of the most important and frequently used materials for construction, steel and concrete represented the highest relative contribution with proportions of 49% and 13%, respectively, cumulatively accounting for approximately 2/3 of the total carbon emissions. The transportation of construction equipment and building materials played a major role in the uncertainty analysis with CVs of 24% and 20%, respectively.

[Fig. 2](#) shows the distribution of all construction activities in the parameter categorization coordinate. Each point in the figure represents one certain construction activity. Most construction activities converged on the area with an uncertainty interval of 15%–20% and a contribution of 0%–1%. To comprehensively investigate the effect of changes in uncertainty and contribution on the determination of critical construction activities, this study identified the key parameters by considering the different levels of contribution and uncertainty. Given the aforementioned converged area and the results obtained in [Table 6](#), we established 12 scenarios. The minimum value for each scenario in terms of their contribution and uncertainty is listed in the first two columns of [Table 7](#).

[Table 7](#) shows the results of the scenario analysis (10,000 runs MCS). Scenarios 1, 2, and 3 revealed that the number of key parameters decreased dramatically when the uncertainty increased. Electricity use and a number of building materials were defined as key parameters at above the 0.1% level of contribution. Considering that several building materials, such as aluminum and polyamide safety netting, have a relatively small weight (<0.1%) while a significant quantity of GHG (2%–3%) is released during the construction phase, alternatives

with low carbon intensity should be selected. When the frequency of occurrence for each key parameter was considered (see Fig. 3), steel was regarded as the key parameter in eight scenarios, followed by concrete, aluminum, and glass in six

Table 4

Result of DQI analysis for emission factor parameters.^a

GHG emissions related construction activities	Number of emission factors	Measurement method	Data source	Geographic representativeness	Technical representativeness	Temporal representativeness
Fuels use in construction equipment	6	Data estimated based on measurements (3)	China Energy Statistical Yearbook 2007 (5)	National data (2)	Data from process related of enterprises with similar technology (2)	Less than 6 (4)
Onsite welding and cutting	1		Chemical formula (5)	Field survey/measure data (5)	Data from process studied of the enterprise with same technology (5)	Less than 3 (5)
Temporary septic-tank	1	Data estimated partly based on	IPCC 2006 (5)	International data (1)	Data from process related of enterprises with	Less than 6 (4)

		assumptions			similar	
		(2)			technology (2)	
Office	1		2009	Data from an area	Data from process	Less than 3
electricity use	1		NDRC	with similar	studied of the	(5)
Construction			Report ^b	production	enterprise with	
electricity			(5)	condition (4)	similar technology	
use					(4)	
Building	79		Ecoinvent	International	Data from process	Less than 6
materials	12		v2.0	data (1)	related of	(4)
production			database		enterprises with	
Building			(5)		similar technology	
materials					(2)	
transportation						
Construction	9					
equipment						
transportation						
Fuels used in	3					
staff						
transportation						
Construction	1	Data	Guidelines			Less than 3
water		estimated	2010 ^c (5)			(5)
production		based on				

			measurements		
			(3)		
Office water	1				
production					
Office cooking	3		China	National data (2)	Less than 6
oil use	3		Energy		(4)
Onsite cooking			Statistical		
oil use			Yearbook		
			2007 (5)		
Offsite septic-	1	Data estimated	IPCC	International	
tank		partly based on	2006 (5)	data (1)	
		assumptions			
		(2)			

a

The number list in “()” is the DQI score.

b 2009 NDRC Report of Emission Factors for Chinese

Regional Power Grid.

c

Guidelines to Account for and Report on GHG Emissions and Removals for Buildings in Hong Kong 2010 scenarios. The result further demonstrated the important status of these four types of building materials in CO₂ emissions during building construction. Two scenarios did not display any result under the assumption that the contribution proportion is more than 10% and the CV is more than 19%. This condition verifies that

because of great efforts in data collection and consolidation, this study can improve the data quality and minimize the possible uncertainties. Considering the change trends of key parameters in 12 scenarios, the proportion of 1% in contribution analysis and a CV of 18% in uncertainty analysis can be selected as the basic value to

Table 5

Result of DQI analysis for elementary flow data.^a

GHG emissions related construction activities	Number of activities	Measurement method	Data source	Geographic representativeness	Technical representativeness	Temporal representativeness
Fuels use in construction equipment	7	Data estimated partly based on assumptions	Contractor's report (4)	Field survey/measure data (5)	Data from process studied of the enterprise with same technology (5)	Less than 3 years (5)
Onsite welding and cutting	17	(2) Data estimated based on measurements				
Temporary septic-tank	8	Data estimated partly based on assumptions				
Office electricity use	29	Consistently measured data	Accounting receipt (5)			
Construction electricity use	29	(5)				

Building	79	Data	Bill of quantity		Data from process
materials	24	estimated	(3)		studied of the
production	19	partly based			enterprise with
Building		on	Secondary	Data from an area	similar technology
materials		assumptions	data from the	with similar	(4)
transportation		(2)	procurement	production	
Construction				condition (4)	
equipment					
transportation					
Fuels used in	15		agency (1)		
staff					
transportation					
Construction	15	Consistently	Accounting	Field	Data from
water	29	measured	receipt (5)	survey/measure	process studied
production	29	data (5)		data (5)	of the enterprise
Office water	29	Regularly			with same
production		measured			technology (5)
Office cooking		data (4)			
oil use					
Onsite cooking					
oil use					
Offsite septic-	2	Regularly	Accounting		
tank		measured	receipt (5)		
		data (4)			

a

The number list in “()” is the DQI score.

Table 6

Results of contribution analysis and uncertainty analysis.

Construction activities	Contribution	Construction activities	Uncertainty
-------------------------	--------------	-------------------------	-------------

1	Steel	48.95%	Construction equipment transportation (7.5~16t)	24.77%
2	Concrete	13.24%	Company cars	24.73%
3	Talcum powder	8.79%	Construction equipment transportation (16~32t)	24.65%
4	U. F. foamed plastic	5.26%	Construction equipment transportation (3.5~7.5t)	24.64%
5	Polyamides safety net	2.79%	Building materials production (>32t)	20.82%
6	Onsite electricity use	2.42%	Building materials transportation 16~32t	20.72%
7	Cement	2.12%	Building materials transportation 3.5~7.5t	20.63%
8	Aluminum	2.00%	Building materials transportation 7.5~16t	20.61%
9	Offsite electricity use	1.52%	Concrete block	19.21%
10	Glass	1.07%	Timber	19.21%

determine the input parameters that need special attention and careful processing. Therefore, eight building materials not only generated large amount of GHG emissions but also represented a high level of uncertainty in the final output. These materials are steel, concrete, talcum powder, U. F. foamed plastic, polyamide safety netting, cement, aluminum, and glass.

Fig. 4 shows the results of MCS in terms of the total GHG emissions. The mean value of MCS was 8791.5 tonnes of carbon dioxide equivalent (CO_{2e}), which was in line with the deterministic result of 8779.4 tonnes of CO_{2e}. The standard deviation and CV for the total emissions were 863.1 and 9.8% respectively, revealing that the uncertainties from the input parameters in this study were acceptable. According to the uncertainty results, a confidence interval within a 90% certainty was estimated from 7422.3 tonnes of CO_{2e} to 10,202.7 tonnes of CO_{2e} with the range width of 2780.4 tonnes of CO_{2e}.

Table 8 shows the GHG emission intensity of different buildings in China. Given the geographic and structural similarities of these buildings, the estimated GHG emission intensity was highly consistent with the findings summarized in Table 8, especially with the building cases analyzed in Shenzhen and Hong Kong. Chang et al. (2016) conducted a disaggregated IeO analysis to quantify the GHG emission for different types of buildings at the national average level. Such benchmark provides a macro-level perspective to examine the reliability of results obtained in present study. Given the emission intensity provided by Chang et al. (2016) for the category of urban residential and office buildings, the result obtained from the uncertainty analysis framework in this study was also acceptable and reasonable.

Fig. 5 shows the trend of convergence for the total GHG emissions with the increasing number of iterations. The mean value of the total amount of emissions became stable after 4500 simulations were run, whereas the standard deviation converged significantly from 5500

iterations. Therefore, the result of MCS with 10,000 runs can be considered effective and valid to reflect the real amount of GHG emissions from the building construction phase.

6. Discussions and policy implications

The uncertainty analysis for LCA is scarcely conducted in the construction industry because the actual process data for building products are often irreproducible and unavailable. As such, the related data and results are limited. This study mitigates such problem by developing an uncertainty assessment framework with the combination of qualitative and quantitative approaches. The framework switches the focus of concern from the contribution-oriented analysis in traditional GHG assessment toward the uncertainty effect examination. The results obtained in this study further emphasize the importance of identifying the uncertainty factors in GHG emission assessment.

In addition to the exploration of typical carbon-intensive construction activities according to their significant emission contributions, this study also provides evidence for the uncertainty-related sensitive factors for assessing GHG emissions.




Fig. 2. Distribution of construction activities in parameter categorization coordinate.

Table 7

Result of scenario analysis.






	Contribution	Uncertainty	Key parameters	Distribution
1	>0.1%	>15%	Onsite electricity use; Offsite electricity use; Steel; Concrete; Talcum powder; U. F. foamed plastic; Polyamides safety net; Cement; Aluminum; Glass; Slag; Clay haydite; Welding rod; Polyurethane; Perlite; Timber plates; Wire entanglement; Formwork; UPVC pipe; Marble; Gravel; Ceramic;	
2	>0.1%	>18%	Steel; Concrete; Talcum powder; U. F. foamed plastic; Polyamides safety net; Cement; Aluminum; Glass; Slag; Clay haydite; Welding rod; Polyurethane; Perlite; Timber plates; Wire entanglement; Formwork; UPVC pipe; Marble; Gravel; Ceramic;	
3	>0.1%	>19%	Aluminum; Glass; Slag; Timber plates; Gravel;	
4	>1%	>15%	Steel; Concrete; Talcum powder; U. F. foamed plastic; Polyamides safety net; Cement; Aluminum; Glass;	
5	>1%	>18%	Steel; Concrete; Talcum powder; U. F. foamed plastic; Polyamides safety net; Cement; Aluminum; Glass;	

Table 7(continued)








	Contribution	Uncertainty	Key parameters	Distribution
6	>1%	>19%	Aluminum; Glass;	
7	>10%	>15%	Steel; Concrete;	
8	>10%	>18%	Steel; Concrete;	
9	>10%	>19%	NULL	
10	>25%	>15%	Steel	

Table 7 (continued)

	Contribution	Uncertainty	Key parameters	Distribution
11	>25%	>18%	Steel	
12	>25%	>19%	Null	

Traditionally, steel and concrete are regarded as the major CO₂ contributors owing to their carbon-intensive manufacturing process. The result of the scenario analysis indicated that aluminum, glass, slag, timber, and gravel are also important, especially considering the effect of their uncertainty (>19%). Given the basic characteristics of building construction, the data measurement for inventory analysis is a significant uncertainty source that influences emission evaluation. Most material flow data are collected or calculated based on the bill of quantities, originally compiled and pre-estimated under numerous assumptions. The quantity changes in the adopted materials and fuels due to wastage, reconstruction,




Fig. 3. Frequency of occurrence for key construction activities in 12 scenarios.

and unexpected events in the construction site may suffer from a high level of uncertainty, thereby underestimating the actual GHG emissions. Furthermore, the emission factors lack the consideration of regional diversity and case-specificity, which has weakness in technical and geographical representativeness to reflect the current GHG emission status in China. Although the carbon emissions generated from the construction practice have been

extensively studied in China, no uniform, authoritative, and official emission factor database applicable for such context has been established. The major barriers for regional specific data measurement include the complexity of geographical conditions, the variation in climate zones, and the differences in manufacturing technologies. Therefore, the corresponding strategies that can holistically mitigate the uncertainty that emanates from building construction should be developed and implemented.

First, to address the temporal uncertainty during assessment, the validity of time period applicable for the corresponding analysis should be indicated. The length of valid time is critical because the assessment result with a short temporal validity reinforces the accuracy level under the current production technology but restrains the future use of such study. Therefore, one compromise for such dilemma is to integrate the national average data from IoO analysis into a process-based model. In this situation, the result can include the case-specific information on actual material inputs and the emission outputs of unit primary process, and it can also reflect the national technology progress in a fixed period.

Second, the national level variations during production may be caused by the different levels of technology and economic development. Therefore, such discrepancy can be reduced by using region-specific production data. For instance, this study utilizes the international emission factors to extrapolate GHG emissions generated from the target building to establish a general situation to examine the effect of data geographic representativeness on the accuracy of final results. However, the overdependence of international data has a disadvantage in reflecting the real situation of




Fig. 4. Monte Carlo simulation result for total GHG emissions.

Table 8

GHG emission intensity obtained in previous research.

Source	Location	Building type	Structure	Gross floor area (m ²)	Assessment model	GHG emissions (tCO ₂ e/m ²)
Xing et al. (2008)	Shanghai	Office	RC	34,620	Process-based	0.606
			SF	46,240		0.315
Wu et al. (2012)	Dalian	Office	RC	36,500	Process-based	0.803
Wang et al. (2016)	Shenzhen	Office	RC	25,023.9	Process-based	1.183

Yan et al. (2010)	Hong Kong	Commercial	RC	43,210	Process-based	0.525
Mao et al. (2013)	Shenzhen	Residential	FSS	216,000	Process-based	0.348
Liu et al. (2009)	Beijing	Residential	FSS	35,356	Process-based	0.374
	Beijing	Residential	FSS	33,290		0.49
	Beijing	Office	RC	91,371		0.541
Gao (2012)	Jiangsu	Residential	FSS	5644e28032	Process-based	0.326
	Jiangsu	Residential	RC	1176e8809		0.273
Yao (2013)	Wuhan	Office	RC	5712e41260	Process-based	0.271e0.48
Chang et al. (2016)	China	Urban Residential Office	e e	e	IeO based	0.260 0.320
Present study	Guangzhou	Residential commercial	RC	11,508	Process-based	0.645e0.887*

Note: “RC” represents the reinforced concrete frame; “SF” represents the steel-framed structure “FSS” represents the frame-shear wall structure; “*” represents that this result was obtained with the confidence interval of 90%.

GHG emission status in China's construction industry. Therefore, to reflect the real transition of China's building emission patterns, this study collected emission factors for primary construction activities based on the data measured and estimated in the context of China (see [Table 9](#)). The results show that the target building generated 8962.3 tonnes of CO₂e to 9491.3 tonnes of CO₂e according to different data sources collected in [Table 9](#) that is 2.1%–8.1% higher than the deterministic result and 1.9%–8.0% higher than the mean value of MCS. Such fluctuation of value is still consistent with the CV (9.8%), demonstrating the validity of the uncertainty analysis




Fig. 5. The trend of convergence of mean and SD for the total GHG emissions.

framework developed in this study. Most importantly, the total amount of emissions estimated according to China's construction practice is higher than the international level, implying the importance of using localized emission factors.

Third, besides the geographic uncertainty at the international level, intra-national difference has also been emphasized in previous studies ([Williams et al., 2009](#)). Such variation is exaggerated in China owing to its imbalanced regional economic development. A promising solution is to identify the major material supply regions according to the material flows in the upstream supply chain of China's construction industry ([Hong et al., 2016b](#)). Therefore, the focus of concern can be narrowed into only several typical resource-supply regions, allowing

the leading authority to establish an emission factor database by only investigating the resourceabundant suppliers.

Fourth, given a high level of uncertainties generated from data measurement, adopting a precast construction or an industrialization building system is an effective means to improve data accuracy. Compared with conventional construction technologies, prefabrication provides a standard, resource-efficient, and modular construction process that can not only minimize the waste and resource depletion during manufacturing but also reduce

Table 9

Emission factors collected in the context of China.

	Unit	Emission factor	Data source
Onsite construction			
equipment use			
Diesel	kgCO ₂ /kg	2.17e3.78	[1]e[7]
Onsite			
electricity use			
Electricity	kgCO ₂ /KWh	0.700e0.953	[1]e[7]
Onsite water			
use			[3]e[5],
Water	kgCO ₂ /m ³	0.259e0.414	[7]
Transportation			[1],
Road			[3],
transportation	kgCO ₂ /tkm	0.159e0.227	[5], [6]

Materials

production

Steel	kgCO ₂ /kg	1.33e2.60	[1]e[7]
Concrete	kgCO ₂ /m ³	251e425	[1]e[7]
Cement	kgCO ₂ /kg	0.698e1.035	[1]-[7]
Aluminum	kgCO ₂ /kg	26.0e29.8	[1]e[5]
Glass	kgCO ₂ /kg	1.10e2.82	[1]e[7]
UPVC pipe	kgCO ₂ /kg	4.65e4.70	[1], [3], [5]
Gravel	kgCO ₂ /kg	0.002	[4], [5]
Ceramic	kgCO ₂ /kg	0.740	[1], [3]e[5]

Source: [1] [Liu et al. \(2009\)](#); [2] [Li \(2010\)](#); [3] [Gao \(2012\)](#); [4] [Yao \(2013\)](#); [5] [Wang et al. \(2016\)](#); [6] [Yan et al. \(2010\)](#); [7] [Mao et al. \(2013\)](#).

reconstruction and unexpected events in the construction site ([Hong et al., 2016a](#)). As such, the preliminary estimation of the material inventory flow through the bill of quantity can relatively reflect the actual materials used during building construction.

7. Conclusions

This study develops a multi-method-based uncertainty analysis framework and quantifies the uncertainty associated with GHG inventories in building construction in China. This framework integrates the deterministic and probabilistic approaches to facilitate the uncertainty

assessment in quantifying carbon emissions and to provide insights into the sensitive construction activities from the uncertainty perspective. Based on the uncertainty analysis framework and case study, four important findings of this study are listed as follows:

- (1) The uncertainty in measurement method and geographic representativeness is considered the major uncertainty source for elementary flow estimation and emission factor collection during building construction.
- (2) The total GHG emissions obtained from the analytical framework for the target building was 8791.5 tonnes of CO₂e with a CV of 9.8%, which was in line with the result calculated by the deterministic method and the result extrapolated based on the data collected from China.
- (3) Apart from the sensitive parameters explored in the traditional uncertainty analysis, the result of the scenario analysis showed that aluminum, glass, slag, timber, and gravel are also important, especially considering the effect of their uncertainty (>19%).
- (4) According to the parameter coordinate in the scenario analysis, the proportion of 1% in contribution analysis and the CV of 18% in uncertainty analysis can be regarded as the baseline for determining the critical input parameters. Under this assumption, steel, concrete, talcum powder, U. F. foamed plastic, polyamide safety netting, cement, aluminum, and glass are the key parameters that should be given due attention.

This study can reinforce the importance of measuring uncertainties in LCA studies and can avoid the misinterpretation of the final results during the decision-making process. In addition, the integration of qualitative and quantitative assessment methods provides a possible solution for assessing the uncertainty of LCA studies in the construction practice. This method also provides a sufficient understanding on the uncertainty related to building construction.

Moreover, this study identifies the critical parameters that influence the GHG emissions during building construction in the context of China. However, it should be noticed that insufficient number of construction projects was investigated in this study. Future studies should be conducted to validate the developed uncertainty analysis framework through investigating various types of construction projects around the world.

Acknowledgements

The authors wish to express their sincere gratitude to the Research Grants Council of Hong Kong and the Research Institute of Sustainable Urban Development of The Hong Kong Polytechnic University for funding the research project on which this paper is based. Appreciation is also due to all members of the research team for their invaluable contribution.

References

- Andre, J.C., Lopes, D.R., 2012. On the use of possibility theory in uncertainty analysis of life cycle inventory. *Int. J. Life Cycle Assess.* 17, 350e361.
- Aye, L., Ngo, T., Crawford, R., Gammampila, R., Mendis, P., 2012. Life cycle greenhouse gas emissions and energy analysis of prefabricated reusable building modules. *Energy Build.* 47, 159e168.
- Basset-Mens, C., van der Werf, H., Durand, P., Leterme, P., 2004. Implications of uncertainty and variability in the life cycle assessment of pig farming systems, complexity and integrated resources management. In: *Proceedings of the 2nd Biennial Meeting of the International Environmental Modelling and Software Society.*

- Basson, L., Petrie, J., 2004. An integrated approach for the management of uncertainty in decision making supported by LCA-based environmental performance information, complexity and integrated resources management. In: Proceedings of the 2nd Biennial Meeting of the International Environmental Modelling and Software Society.
- Canter, K.G., Kennedy, D.J., Montgomery, D.C., Keats, J.B., Carlyle, W.M., 2002. Screening stochastic life cycle assessment inventory models. *Int. J. Life Cycle Assess.* 7, 18e26.
- Cellura, M., Longo, S., Mistretta, M., 2011. Sensitivity analysis to quantify uncertainty in life cycle assessment: the case study of an Italian tile. *Renew. Sustain. Energy Rev.* 15, 4697e4705.
- Chang, Y., Huang, Z., Ries, R.J., Masanet, E., 2016. The embodied air pollutant emissions and water footprints of buildings in China: a quantification using disaggregated input-output life cycle inventory model. *J. Clean. Prod.* 113, 274e284.
- Chang, Y., Ries, R.J., Man, Q., Wang, Y., 2014. Disaggregated IO LCA model for building product chain energy quantification: a case from China. *Energy Build.* 72, 212e221.
- Chen, G.Q., Zhang, B., 2010. Greenhouse gas emissions in China 2007: inventory and input-output analysis. *Energy Policy* 38, 6180e6193.
- Chevalier, J.-L., Le Teno, J.-F., 1996. Life cycle analysis with ill-defined data and its application to building products. *Int. J. Life Cycle Assess.* 1, 90e96.
- Ciroth, A., Hagelüken, M., Sonnemann, G.W., Castells, F., Fleischer, G., 2002. Geographical and technological differences in life cycle inventories shown by the use of process models for waste incinerators part I. technological and geographical differences. *Int. J. Life Cycle Assess.* 7, 295e300.

- Coulon, R., Camobreco, V., Teulon, H., Besnainou, J., 1997. Data quality and uncertainty in LCI. *Int. J. Life Cycle Assess.* 2, 178e182.
- Cowles, M.K., Carlin, B.P., 1996. Markov chain Monte Carlo convergence diagnostics: a comparative review. *J. Am. Stat. Assoc.* 91, 883e904.
- Gao, X., 2012. *Assessment Methodology and Empirical Analysis of Embodied Carbon Footprint of Building Construction*, Management Science and Engineering. Tsinghua University, Beijing.
- Gavankar, S., Anderson, S., Keller, A.A., 2015. Critical components of uncertainty communication in life cycle assessments of emerging technologies. *J. Industrial Ecol.* 19, 468e479.
- Geisler, G., Hellweg, S., Hungerbühler, K., 2004. Uncertainties in LCA of plantgrowth regulators and implications on decision-making, complexity and integrated resources management. In: *Proceedings of the 2nd Biennial Meeting of the International Environmental Modelling and Software Society*.
- Geisler, G., Hellweg, S., Hungerbühler, K., 2005. Uncertainty analysis in life cycle assessment (LCA): case study on plant-protection products and implications for decision making (9 ppþ 3 pp). *Int. J. Life Cycle Assess.* 10, 184e192.
- Heijungs, R., 1996. Identification of key issues for further investigation in improving the reliability of life-cycle assessments. *J. Clean. Prod.* 4, 159e166.
- Herrmann, I.T., Hauschild, M.Z., Sohn, M.D., McKone, T.E., 2014. Confronting uncertainty in life cycle assessment used for decision support. *J. Industrial Ecol.* 18, 366e379.

- Hong, J., Shen, G.Q., Feng, Y., Lau, W.S.-t., Mao, C., 2015. Greenhouse gas emissions during the construction phase of a building: a case study in China. *J. Clean. Prod.* 103, 249e259.
- Hong, J., Shen, G.Q., Mao, C., Li, Z., Li, K., 2016a. Life-cycle energy analysis of prefabricated building components: an input-output-based hybrid model. *J. Clean. Prod.* 112, 2198e2207.
- Hong, J., Shen, Q., Xue, F., 2016b. A multi-regional structural path analysis of the energy supply chain in China's construction industry. *Energy Policy* 92, 56e68.
- Huijbregts, M.A., Gilijamse, W., Ragas, A.M., Reijnders, L., 2003. Evaluating uncertainty in environmental life-cycle assessment. A case study comparing two insulation options for a Dutch one-family dwelling. *Environ. Sci. Technol.* 37, 2600e2608.
- Huijbregts, M.A., Norris, G., Bretz, R., Citroth, A., Maurice, B., von Bahr, B., Weidema, B., de Beaufort, A.S., 2001. Framework for modelling data uncertainty in life cycle inventories. *Int. J. Life Cycle Assess.* 6, 127e132.
- IEA, 2007. *World Energy Outlook 2007: China and India Insights*. Organisation for Economic Co-operation and Development.
- Imbeault-Tetreault, H., Jolliet, O., Deschênes, L., Rosenbaum, R.K., 2013. Analytical propagation of uncertainty in life cycle assessment using matrix formulation. *J. Industrial Ecol.* 17, 485e492.
- ISO, 2006. *ISO 14064. Greenhouse Gases e Part 1: Specification with Guidance at the Organization Level for Quantification and Reporting of Greenhouse Gas Emissions and Removals*.

- Kennedy, D.J., Montgomery, D.C., Quay, B.H., 1996. Stochastic environmental life cycle assessment modeling: a probabilistic approach to incorporating variable input data quality. *Int. J. Life Cycle Assess.* 1, 199e207.
- Li, B., 2010. Research on the Technology System and the Calculation Method of Carbon Emission of Low-carbon Building, Construction Management. Huazhong University of Science & Technology, Wuhan.
- Liu, N., Wang, J., Li, R., 2009. Computational method of CO₂ emissions in Chinese urban residential communities. *J. Tsinghua Univ. Sci. Technol.* 9, 000.
- Liu, Z., Geng, Y., Lindner, S., Guan, D., 2012. Uncovering China's greenhouse gas emission from regional and sectoral perspectives. *Energy* 45, 1059e1068.
- Lloyd, S.M., Ries, R., 2007. Characterizing, propagating, and analyzing uncertainty in life-cycle assessment: a survey of quantitative approaches. *J. Industrial Ecol.* 11, 161e179.
- Lo, S.-C., Ma, H.-w., Lo, S.-L., 2005. Quantifying and reducing uncertainty in life cycle assessment using the Bayesian Monte Carlo method. *Sci. total Environ.* 340, 23e33.
- Mao, C., Shen, Q., Shen, L., Tang, L., 2013. Comparative study of greenhouse gas emissions between off-site prefabrication and conventional construction methods: two case studies of residential projects. *Energy Build.* 66, 165e176.
- Maurice, B., Frischknecht, R., Coelho-Schwartz, V., Hungerbühler, K., 2000. Uncertainty analysis in life cycle inventory. Application to the production of electricity with French coal power plants. *J. Clean. Prod.* 8, 95e108.
- May, J.R., Brennan, D.J., 2003. Application of data quality assessment methods to an LCA of electricity generation. *Int. J. Life Cycle Assess.* 8, 215e225.

- Metz, B., Davidson, O.R., Bosch, P.R., Dave, R., Meyer, L.A., 2007. Contribution of Working Group III to the Fourth Assessment Report of the Intergovernmental Panel on Climate Change.
- Shen, L., Lu, W., Peng, Y., Jiang, S., 2011. Critical assessment indicators for measuring benefits of rural infrastructure investment in China. *J. Infrastructure Syst.* 17, 176e183.
- Sonnemann, G.W., Schuhmacher, M., Castells, F., 2003. Uncertainty assessment by a Monte Carlo simulation in a life cycle inventory of electricity produced by a waste incinerator. *J. Clean. Prod.* 11, 279e292.
- Sugiyama, H., Fukushima, Y., Hirao, M., Hellweg, S., Hungerbühler, K., 2005. Using standard statistics to consider uncertainty in industry-based life cycle inventory databases (7 pp). *Int. J. Life Cycle Assess.* 10, 399e405.
- Tan, R.R., Briones, L.M.A., Culaba, A.B., 2007. Fuzzy data reconciliation in reacting and nonreacting process data for life cycle inventory analysis. *J. Clean. Prod.* 15, 944e949.
- Tan, R.R., Culaba, A.B., Purvis, M.R., 2002. Application of possibility theory in the life-cycle inventory assessment of biofuels. *Int. J. Energy Res.* 26, 737e745.
- Venkatesh, A., Jaramillo, P., Griffin, W.M., Matthews, H.S., 2010. Uncertainty analysis of life cycle greenhouse gas emissions from petroleum-based fuels and impacts on low carbon fuel policies. *Environ. Sci. Technol.* 45, 125e131.
- Wang, E., Shen, Z., 2013. A hybrid Data Quality Indicator and statistical method for improving uncertainty analysis in LCA of complex system: application to the whole-building embodied energy analysis. *J. Clean. Prod.* 43, 166e173.

- Wang, T., Seo, S., Liao, P.-C., Fang, D., 2016. GHG emission reduction performance of state-of-the-art green buildings: review of two case studies. *Renew. Sustain. Energy Rev.* 56, 484e493.
- Weidema, B.P., 1998. Multi-user test of the data quality matrix for product life cycle inventory data. *Int. J. Life Cycle Assess.* 3, 259e265.
- Weidema, B.P., Wesnæs, M.S., 1996. Data quality management for life cycle inventories dan example of using data quality indicators. *J. Clean. Prod.* 4, 167e174.
- Williams, E.D., Weber, C.L., Hawkins, T.R., 2009. Hybrid framework for managing uncertainty in life cycle inventories. *J. Industrial Ecol.* 13, 928e944.
- Wu, H.J., Yuan, Z.W., Zhang, L., Bi, J., 2012. Life cycle energy consumption and CO₂ emission of an office building in China. *Int. J. life cycle Assess.* 17, 105e118.
- Xing, S., Xu, Z., Jun, G., 2008. Inventory analysis of LCA on steel-and concrete construction office buildings. *Energy Build.* 40, 1188e1193. Xu 1985: The method of Monte Carlo, Science and Technology, Shanghai (in Chinese).
- Yan, H., Shen, Q., Fan, L.C., Wang, Y., Zhang, L., 2010. Greenhouse gas emissions in building construction: a case study of One Peking in Hong Kong. *Build. Environ.* 45, 949e955.
- Yao, X., 2013. Study on Calculation of Carbon Emissions Baseline of Public Building Based on LCA, Environmental Engineering. Huazhong University of Science & Technology, Wuhan.