



Available online at www.sciencedirect.com



Procedia

Energy Procedia 105 (2017) 335 – 342

The 8th International Conference on Applied Energy – ICAE2016

Termination control temperature study for an air source heat pump unit during its reverse cycle defrosting

SONG Mengjie^{a,*}, WANG Xuanjie^b, LIAO Liyuan^a, DENG Shiming^c

^a Department of Energy Engineering, School of Materials and Energy, Guangdong University of Technolog, Guangzhou, China ^bDepartment of Mechanical and Aerospace Engineering, The Hong Kong University of Science and Technology, Kowloon, Hong Kong SAR

^c Department of Building Services Engineering, The Hong Kong Polytechnic University, Kowloon, Hong Kong SAR

Abstract

For an air source heat pump (ASHP) unit with a vertically installed multi-circuit outdoor coil, a reverse cycle defrosting (RCD) operation is always terminated when the tube surface temperature at the exit of the lowest circuit reaches a pre-set value. It is obviously that when the pre-set temperature is higher, the defrosting duration would be prolonged. Not only more energy would be consumed on heating cold ambient air, but also the occupants' thermal comfort adversely affected. However, if the pre-set temperature is lower, more residual water would be left on the downside surface of fin in an outdoor coil, which degrades the system performance during the next frosting/defrosting cycle. In order to find a suitable DTT or its range, in this paper, an experimental investigation on RCD operation for an ASHP unit with a multi-circuit outdoor coil was conducted and reported. As concluded, DTT is suitable at the range of 20-25 °C, around 22 °C.

© 2017 The Authors. Published by Elsevier Ltd. This is an open access article under the CC BY-NC-ND license (http://creativecommons.org/licenses/by-nc-nd/4.0/).

Peer-review under responsibility of the scientific committee of the 8th International Conference on Applied Energy.

Keywords: Air source heat pump; Multi-circuit outdoor coil; Reverse cycle defrosting; Defrosting termination temperature; Experimental study

1 Introduction

Air source heat pump (ASHP) units have been widely used as cooling and heating sources for heating, ventilation and air conditioning installations over the recent decades in many parts of the world because of their advantages such as energy saving, environmental protection and flexibility. However, when an ASHP unit works in heating mode at high humidity and low temperature environment in winter, it is difficult to avoid frost formation and accumulation on its surface of outdoor coil. The frost layer degrades

1876-6102 © 2017 The Authors. Published by Elsevier Ltd. This is an open access article under the CC BY-NC-ND license (http://creativecommons.org/licenses/by-nc-nd/4.0/).

^{*} Corresponding author. Tel./fax: +86 20 39322581

E-mail address: Mengjie.Song@gmail.com.

system heating/frosting performance and even results in an unexpected shutdown of the ASHP unit. Therefore, periodic defrosting becomes necessary [1].

Currently, there are many defrosting methods, such as 1) compressor shut-down defrosting [2], 2) electric heating defrosting [3,4], 3) hot water spray defrosting [5], 4) hot gas by-pass defrosting [6,7], 5) compressed air blowing defrosting [8,9], 6) ultrasonic vibration defrosting [10,11], etc. However, among these used methods, the most widely used standard defrosting method is reverse cycle defrosting (RCD). When a space heating ASHP unit is operated at a RCD mode, its outdoor coil acts as a condenser and its indoor coil acts as an evaporator [12]. It should be noted that for defrosting on ASHP unit, a complete defrosting process covers both melting frost and drying coil surface. For an outdoor coil used in an ASHP unit, on its refrigerant side, multi-circuit structures are commonly used for minimizing refrigerant pressure loss and enhancing heat transfer efficiency. To save more floor space, a multi-circuit outdoor is always vertically installed. Authors have carried out series experimental and numerical studies to improve the RCD performance of an ASHP unit with a multi-circuit outdoor coil, by eliminating the negative effects of melted frost [12-14], improving the frosting evenness values [15-17], optimizing the refrigerant distribution [18,19], and adjusting the installation style of outdoor coil [20,21], etc.

For an ASHP unit with a vertically installed multi-circuit outdoor coil, a RCD operation is always terminated when the tube surface temperature at exit of the lowest circuit reaches a pre-set value. It is obviously that when the pre-set temperature is higher, the defrosting duration would be prolonged. Not only more energy would be consumed on heating cold ambient air, but also the occupants' thermal comfort adversely affected [22]. Since the ambient air temperature is always at the lowest value at night, sleep thermal comfort problem due to the degraded performance of air conditioning system attract scholar's attentions [23-25]. On the contrary, if the pre-set temperature is lower, more residual water would be left on the surface of outdoor coil, which degrades the system performance during the next frosting/defrosting cycle [26]. In the open literatures, a suitable pre-set temperature, working as defrosting termination temperature (DTT) of a RCD operation, was not fixed. For example, used values consist of 10 °C [27], 12 °C [28], 15 °C [29], 18 °C [30], 20 °C [31], 24 °C [12-21], 26.7 °C [32], and 35 °C [33], etc. Consequently, in order to find a suitable DTT or its range, in this paper, an experimental investigation on RCD operation for an ASHP unit with a multi-circuit outdoor coil was conducted. This study makes contributions on the method to find a suitable DTT for RCD of ASHP units.

2 Experimentation

2.1. Experimental ASHP unit

An experimental ASHP unit was specifically established for carrying out the experimental work reported in this paper. The experimental ASHP unit was installed in an existing environmental chamber having a simulated indoor heated space and a simulated outdoor frosting space. Fig. 1 shows the schematics of the ASHP unit installed in the environmental chamber. The outdoor coil was specially designed and made for this study, as shown in Fig. 2.

2.2. Experimental procedures and conditions

Relative detailed information about the equipment is shown in References [12-14], including experimental procedures and conditions. Specially, in this study, only one experimental case was carried





Fig. 1 Schematics of the experimental ASHP unit installed in an environmental chamber



Fig. 2 Details of the three-parallel refrigerant circuit outdoor coil and locations of solenoid valves and manual stop valves

3 Results

As shown in Fig. 3, five phases were divided with six nodes, and Node 1 to 6 are at 10, 15, 20, 25, 30, and 35 °C, respectively. The six nodes are directly corresponding to the time of 151, 158, 172, 189, 211, 235 s, respectively. Fig. 4 shows the measured fin surface temperature at the centre of each circuit of outdoor coil. Clearly, the temperature range is changed from 10-35 °C to 6.2-31.2 °C. Temperature difference of P3 is the biggest, at 6.6 °C.

In addition, Figs. 5-10 show the other several operating parameters of system during RCD. Table 1 summarizes the DTT phase and nodes from the special points of different parameters. From these analysed special values in the following six figures, it is seems that the tube surface temperature at 175 s, about 22 °C in Fig. 3, could reflect the most suitable DTT. Therefore, it is demonstrated that, the most suitable DTT is about 22 °C, and the range is P3, 20-25 °C, in this study.



Fig. 4 Measured fin surface temperature at the centre of each circuit of outdoor coil



Fig. 5 Measured temperatures of compressor suction and discharge



Fig. 7 Total inputs coming from outside of system



Fig. 9 Measured temperature of air surrounding each circuit



Fig. 6 Total energy coming from outside of system



Fig. 8 Measured temperatures of tube surface at entrance and exit of outdoor coil



Fig. 10 Measured refrigerant volumetric flow rate

Item	Parameter	Duration
1	Total energy coming from outside of system	165 s -
2	Total inputs coming from outside of system	170 s -
3	Compressor suction temperature	170 s - 190 s
4	Average of fin surface temperature	172 s - 189 s
5	Temperature of air surrounding outdoor coil	172 s - 185 s
6	Tube surface temperature at the exit of outdoor coil	175 s
7	Measured refrigerant volumetric flow rate	175 s

Table 1 DTT phase and node from different parameters

4 Conclusions

For an ASHP unit with a vertically installed multi-circuit outdoor coil, a suitable DTT can effectively improve the frosting/defrosting operation performances. To find a suitable DTT or its range, an experimental investigation on RCD operation was conducted. Five phases were firstly divided with six tube surface temperature nodes. This was followed by analyzing experimental results, such as temperatures of fin surface and surrounding air, total energy, refrigerant flow rate, etc. Finally, the conclusion that DTT is suitable at 20-25 °C, around 22 °C, was given. In addition, using this method, suitable RCD DTTs could also be reached for other ASHP units. Consequently, saving more energy for ASHP units could be expected.

Acknowledgements

This work was supported by the National Natural Science Foundation of China under Grant No. 51606044, the One-Hundred Young Talents Project of Guangdong University of Technology (Type B) under Grant No. 220413529, and The Hong Kong Polytechnic University.

References

[1] Song MJ, Pan DM, Li N, Deng SM. An experimental study on the negative effects of downwards flow of the melted frost over a multi-circuit outdoor coil in an air source heat pump during reverse cycle defrosting. *Appl Energy* 2015; **138**: 598-604.

[2] Ameen FR, Coney JER, Sheppard CGW. Experimental study of warm-air defrosting of heat-pump evaporators. *Int J Refrig* 1993; **16** :13-18.

[3] Bansal P, Fothergill D, Fernandes R. Thermal analysis of the defrost cycle in a domestic freezer. *Int J Refrig* 2010; **33**: 589-599.

[4] Melo C, Knabben FT, Pereira PV. An experimental study on defrost heaters applied to frost-free household refrigerators. *Appl Ther Eng* 2013; **51** :239-245.

[5] Abdel-Wahed RM, Hifni MA, Sherif SA. Hot water defrosting of a horizontal flat plate cooling surface. *Int J Refrig* 1983; 6: 152-154.

[6] Choi HJ, Kim BS, Kang D, Kim KC. Defrosting method adopting dual hot gas bypass for an air-to-air heat pump. *Appl Energy* 2011; **88**: 4544-4555.

[7] Krakow KI, Lin S. Hot-gas bypass defrosting of evaporators utilizing a vaporizer. ASHRAE Trans 1996; 102: 385-394.

[8] Aihara T, Taku O, Toshiyuki S, Hitoshi K. Heat-transfer and defrosting characteristics of a horizontal array of cooled tubes immersed in a very shallow fluidized bed. *Int J Heat Mass Tran* 1997; **40**: 1807-1815.

[9] Sonobe N, Fukiba K, Sato S, Yoshimura Y. Method for defrosting heat exchangers using an air-particle jet. Int J Refrig 2015; 60: 261-269.

[10] Wang D, Tao T, Xu G, Luo A, Kang S. Experimental study on frosting suppression for a finned-tube evaporator using ultrasonic vibration. *Exp Therm Fluid Sci* 2012; **36**: 1-11.

[11] Tan HH, Xu GH, Tao TF, Sun XQ, Yao WD. Experimental investigation on the defrosting performance of a finned-tube evaporator using intermittent ultrasonic vibration. *Appl Energy* 2015; **158**: 220-232.

[12] Song MJ, Deng SM, Pan DM, Mao N. An experimental study on the effects of downwards flowing of melted frost over a vertical multi-circuit outdoor coil in an air source heat pump on defrosting performance during reverse cycle defrosting. *Appl Ther Eng* 2014; **67**: 258-265.

[13] Song MJ, Deng SM, Xia L. A semi-empirical modeling study on the defrosting performance for an air source heat pump unit with local drainage of melted frost from its three-circuit outdoor coil. *Appl Energ* 2014; **136**: 537-547.

[14] Song MJ, Mao N, Deng SM, Chen Y, Wang C, Yang QC. Experimental investigations on eliminating surface tension of melted frost for defrosting performance improvement of a multi-circuit outdoor coil. *Appl Ther Eng* 2016; **103**: 1278-1288.

[15] Song MJ, Xia L, Mao N, Deng SM. An experimental study on even frosting performance of an air source heat pump unit with a multi-circuit outdoor coil. *Appl Energy* 2016; **164**: 36-44.

[16] Song MJ, Chen AL, Mao N. An experimental study on defrosting performance of an air source heat pump unit with a multi-circuit outdoor coil at different frosting evenness values. *Appl Ther Eng* 2016; **94**: 331-340.

[17] Song MJ, Mao N, Deng SM, Xia YD, Chen Y. An experimental study on defrosting performance for an air source heat pump unit at different frosting evenness values with melted frost locally drainage. *Appl Therm Eng* 2016; **99**:730-40.

[18] Song MJ, Xia L, Deng SM. A modeling study on alleviating uneven defrosting for a vertical three-circuit outdoor coil in an air source heat pump unit during reverse cycle defrosting. *Appl Energ.* 2016; **161**: 268-278.

[19] Song MJ, Wang ZH, Mao N, Li Z, Chen Y. An experimental study on the uneven refrigerant distribution over a vertically installed multi-circuit outdoor coil in an air source heat pump unit during reverse cycle defrosting. *Appl Ther Eng* 2015;91:975-985.

[20] Song MJ, Deng SM, Mao N, Ye XM. An experimental study on defrosting performance for an air source heat pump unit with a horizontally installed multi-circuit outdoor coil. *Appl Energy* 2016; **165**: 371-382.

[21] Song MJ, Xu XG, Deng SM, Mao N. An experimental study on performance during reverse cycle defrosting of an air source heat pump with a horizontal three-circuit outdoor coil. *Energy Procedia*. 2014; **61**: 92-95.

[22] Qu ML, Xia L, Deng SM, Jiang YQ. Improved indoor thermal comfort during defrost with a novel reverse-cycle defrosting method for air source heat pumps. *Build Environ* 2010; **45**: 2354-2361.

[23] Mao N, Song MJ, Chan MY, Pan DM, Deng SM. Computational fluid dynamics (CFD) modelling of air flow field, mean age of air and CO₂ distributions inside a bedroom with different heights of conditioned air supply outlet. *Appl Energ* 2016; **164**: 906-915.

[24] Mao N, Song MJ, Deng SM, Pan DM, Chen SJ. Experimental and numerical study on air flow and moisture transport in sleeping environments with a task/ambient air conditioning (TAC) system. *Energ Buildings* 2016; **133**: 596-604.

[25] Mao N, Song MJ, Deng SM. Application of TOPSIS method in evaluating the effects of supply vane angle of a task/ambient air conditioning system on energy utilization and thermal comfort. *Appl Energ* 2016; **180**: 536-545.

[26] Li, LT, Wang W, Sun YY, Feng YC, Lu WP, Zhu JH, Ge YJ. Investigation of defrosting water retention on the surface of evaporator impacting the performance of air source heat pump during periodic frosting-defrosting cycles. *Appl Energ* 2014; **135**: 98-107.

[27] Huang D, Li Q, Yuan X. Comparison between hot-gas bypass defrosting and reverse-cycle defrosting methods on an airto-water heat pump. *Appl Energy* 2009; **86**: 1697-1703.

[28] Ding YJ, Ma GY, Chai QH. Experiment investigation of reverse cycle defrosting methods on air source heat pump with TXV as the throttle regulator. *Int J Refrig* 2004; **27**: 617-678.

[29] Wang W, Xiao J, Feng YC, Guo QC, Wang LC. Characteristics of an air source heat pump with novel photoelectric sensors during periodic frostedefrost cycles. *Appl Ther Eng* 2013; **50**: 177-186.

[30] Huang H, Shu PC, Li ZH. Experimental study of operating characteristics under frosting in air source heat pump water chiller/heater. *Fulid Machinery* 1998; **12**: 43-47.

[31] Choi HJ, Kim BS, Kang D, Kim KC. Defrosting method adopting dual hot gas bypass for an air-to-air heat pump. *Appl Energ* 2011; **88**: 4544-4555.

[32] Payne V, O'Neal DL. Defrost cycle performance for an air-source heat pump with a scroll and a reciprocating compressor. *Int J Refrig* 1995; **18**: 107-112.

[33] Dong JK, Jiang YQ, Deng SM, Yao Y, Qu ML. Improving reverse cycle defrosting performance of air source heat pumps using thermal storage-based refrigerant sub-cooling energy. *Building Serv Eng Res Technol* 2012; **33**: 223-236.



Biography

Dr. SONG Mengjie is a young researcher, who graduated from the Hong Kong Polytechnic University, and working as an Associate Professor at the Department of Energy Engineering, Guangdong University of Technology, China. He has wide research interests, consisting of frosting/defrosting for ASHP units, heat and mass transfer around multi-circuit heat exchangers, Phase Change Materials, clean energy system, indoor thermal comfort, and Organic Rankine Cycle, etc.