

Operation management of green ports and shipping networks: overview and research opportunities

Lu Zhen¹, Dan Zhuge² (✉), Liwen Murong³, Ran Yan², Shuaian Wang²

1 School of Management, Shanghai University, Shanghai, China

2 Department of Logistics and Maritime Studies, The Hong Kong Polytechnic University, Hong Kong, China

3 Department of Systems Innovation, the University of Tokyo, Tokyo, Japan

Abstract: Global ports and maritime shipping networks are important carriers for global supply chain networks, but they are also the main sources of energy consumption and pollution. To limit ship emissions in ports and offshore areas, the International Maritime Organization, as well as some countries, has issued a series of policies. This paper highlights the importance and necessity of investigating emergent research problems in the fields of green port and maritime shipping network operations management. Extensive literature related to this topic has been reviewed and discussed in this paper. Moreover, a comprehensive research framework on green port and shipping operations management is proposed for future research opportunities. The framework mainly comprises four research areas related to emission control policies and emission grading policies. This paper may provide some new ideas to the academia and industry practitioners for improving the performance and efficiency of green port and maritime shipping operations management.

Keywords: maritime shipping, port operations, green port, green shipping, emission control areas

1 Introduction

Over 90% of the world's trade is carried by the shipping network (UNCTAD, 2011), which is one of the main impetus of global economic growth and global supply chain network development (Fransoo and Lee, 2013; Lee and Song, 2017). However, numerous emissions of pollutant gases and greenhouse gases are caused by the frequent shipping activity, thus making it one of the main sources of pollution and energy consumption. The development of management science theory and engineering practice have led to the in-depth research on green port and shipping network operations management, mainly to improve productivity and service levels, which then contribute to the development in scientific operation of ports and shipping networks. However, from the perspective of emission control in green port operations, relevant research has not been conducted systematically yet in the academia or by the industry, which means that no comprehensive theory and method of operations management exists for operation efficiency, energy saving, and emission control optimization.

From the perspective of port operators, the following aspects are lacking: a comprehensive evaluation system for the emission footprint analysis of handling activities, effective models of emission load mechanism in container ports, and optimization models for coordinating operation efficiency, energy saving, and emission control. As a result, no scientific mechanism is available for

E-mail: lzhen@shu.edu.cn (L Zhen), dan.zhuge@connect.polyu.hk (D Zhuge)
Tel: +86-21-6613-7932 (L Zhen), +852-2766-7419 (D Zhuge)

controlling emission in ports, given the incomplete information. The logistics activity of ports is related to many logistics activities in sea ports, hinterlands, inland river ports, and road/railway/waterway multimode transportation networks. Hence, a reasonable design of the collection and distribution system is crucial in solving the pollutant-control problem of ports. Moreover, a comprehensive theory needs to be developed immediately to improve the operations management of green ports, optimization in energy-saving measures, and management of port operations. With the aim of grading the emission level of port operations, intelligent transportation mode for port activities needs to be proposed to optimize the layout of logistics operation system in ports, which is also the foundation of scientific development in green ports.

From the perspective of shipping companies, two operation strategies satisfy the standards of Emission Control Area (ECA). The first strategy is to use both the heavy-sulfur fuel and low-sulfur fuel (or marine gas oil, MGO) in sailing. Low-sulfur fuel, despite its high cost, is preferred when sailing in ECAs. The second strategy is to equip the desulfurization facility (i.e., the scrubber), which means that only heavy-sulfur fuel is applied during shipping. If the first strategy is chosen, shipping companies have to use the high-priced low-sulfur fuel or MGO in ECAs, and they will try to minimize the consumption of low-sulfur fuel. If the second strategy is chosen, shipping companies have to upgrade the equipment of fleets and operate them based on fleet construction to save on operation costs. In satisfying ECA standards, shipping companies have to choose different strategies depending on their shipping activities, such as the optimization of vessel speed and the operation method of scheduling fleets, and so on. Therefore, the main obstacle of shipping companies with regard to operations management is the quantitative optimization of shipping networks, namely, the lack of an operations strategy through the application of a mathematical method and an optimization algorithm. Operation costs have to be controlled under the policies of green ports and ECA to ensure the competitiveness of shipping companies.

From the perspective of government regulation departments, little research regarding the formulation of emission control and subsidy policies is available, especially on quantitative methods and models. Further investigation on the supervision and regulation of shipping industry pollutant discharge is needed. Policymakers can analyze the positive and negative impacts of shipping industry on emissions with the aid of emission grading policies based on the dynamic analysis of certain emission control policies. Here the emission grading policies are about dividing the emissions of port operation activities (or shipping activities) into several grades (levels); then different policies of penalty or incentive are designed for different grades. In addition, the global shipping industry is at the period of “post-financial crisis.” Numerous small- and medium-sized companies have chosen to become less competitive, which indicates the timeliness of proposing the emission control policy. To effectively control port operation emissions, models are needed to aid government regulation departments and shipping companies in wisely choosing emission control policies and other subsidy policies.

On the basis of the above discussions, port cities, port operators, shipping companies, and governments need to realize the goal of emission reduction in relation to improving the service level of shipping companies and port operators and controlling overall cost. This paper reviews the literature regarding the field of green port and shipping network operations management and further investigates construction of management optimization theory on green ports and shipping networks.

2 Background

The shipping industry in china has increased rapidly over the past decades. Seven of the top ten biggest ports in the world are located in China. UNCTAD (2015) reported that the global container

throughputs handled in China account for 26.5% in 2014. However, the energy consumption of Chinese ports increased by 112% in 2014 compared with that in 2005, with an average annual growth rate of 8.7%. CO₂ emission increased by 55% in 2014 compared with that in 2005, which is obviously much higher than the average level. These phenomena directly affect economic efficiency and the environment. Moreover, it is evident that the implementation of “One Belt One Road” will further improve the maritime transportation networks as well as import and export trade in China, which could further aggravate air pollution and deteriorate the environment. The ports in China are distributed intensively in the areas of Bohai Rim (BR), Yangtze River Delta (YRD), and Pearl River Delta (PRD), which also have the highest population density. Therefore, air emissions from shipping in these areas may cause more severe environment and health problem. According to the 13th Five-Year Plan, pollutants from port activities have to be regulated in the three areas. By 2020, the overall annual emissions of SO_x, NO_x, and particulate matters (PM) should decrease by 65%, 20%, and 30%, respectively, compared with those in 2015. The Domestic Emission Control Area (DECA) including BR, YRD and PRD has been further extended along the shoreline of China in 2018, and the major rule is that seagoing vessels within the new DECA should use marine fuel with the sulfur content no more than 0.5% since January 1, 2019.

An important issue at the moment is how to achieve the goal of energy saving and emission reduction in ports, and simultaneously improve the service level of these ports. The International Maritime Organization (IMO) has reported that CO₂ emissions from ships account for nearly 2.6% of the world's annual emissions, whereas SO_x emissions and NO_x emissions from ships account for 13% and 15% of the annual emissions from human activities, respectively. Moreover, 70% of ship emissions are emitted in offshore areas shorter than 400 km from land. For example, in Shanghai, emissions from shipping activities account for approximately 12% of the city's emissions. Shipping activities have been the third largest source of air pollution, following those of motor vehicle activities and industrial enterprises. The Intergovernmental Panel on Climate Change (IPCC) has reported that the growth of carbon emissions in the shipping industry is the fastest among global carbon emissions. In 1995, the amount was twice of that in 1990, and it has been predicted that carbon emissions from the shipping industry will increase 10 times by 2050 compared relative to that in 1995. IMO has warned that unregulated carbon emissions from the shipping industry will increase to 12%–18% of the global carbon emissions by 2050 (Buhaug et al., 2009). To control the destructive influence of shipping activities on the climate and the environment, IMO proposes ECA policies that require ships to strictly obey emission control rules in certain jurisdiction areas (IMO, 2008). IMO and some governments, including China, have issued a series of policies to control emissions in ports and offshore areas. Fuel costs account for more than 70% of overall operating costs, which means that these emission control measures will impose considerable burden on the costs of shipping companies. For example, COSCO SHIPPING Group spent RMB 180 million to implement the low-sulfur fuel or ECA in 2015. Therefore, an in-depth research on optimizing resource management and scheduling plans for ports and shipping network under emission control policies is important, with the aim of controlling operating costs while developing green ports. Although emissions from shipping activities have a significant impact on the global environment, regulating emissions during shipping is difficult for multisource owners (Heitmann and Khalilian, 2011). As a result, the optimization research on emission grading and emission control policies and other subsidy policies should be initiated.

3 Related work

The academia has paid considerable attention toward green ports and shipping logistics. Davarzani et al. (2016) proposed a systematic literature review of recent articles regarding green ports and maritime logistics. In this paper, the review will focus on three areas: (i) research on green port

operations management and optimization, (ii) research on optimizing the operations management in green shipping networks, and (iii) research on emission control measures and related policies in green shipping. The relation between these papers is also reflected by the categories, which contains three parts: port, shipping, and policy on port & shipping. The main methodologies for those researches mainly focus on operations research and management sciences (OR/MS).

3.1 Research on green port operations management and optimization

The operation system of container ports is a complicated stochastic dynamic system of activities, including container and vessel handling, truck transportation, and equipment operation (Zhen, 2017). Although the decision problems and related models on optimization are varied and complicated, the aim of these problems is specific and the boundaries are relatively clear. Therefore, the research on operations management of ports has attracted scholars from different fields, such as operations research, systems engineering, computer science, and applied mathematics (Wang et al., 2017). This paper will review the related articles on green ports from the perspective of quayside and yard side operations.

The core problem in quayside operations is the berth allocation problem (BAP), which involves the assignment of location and staying time for visiting ships. BAP is very important because it is the foundation of various scheduling problems in ports. Extensive literature focuses on two types of BAP, i.e., discrete BAP (Imai et al., 2001; Cordeau et al., 2005; Giallombardo et al., 2010) and continuous BAP (Lim 1998; Wang and Lim 2007). Combining BAP with “green” studies is a hot topic in academic and practice. Du et al. (2011) investigated a BAP considering fuel consumption and developed a general power function between fuel consumption rate and speed rate to determine the precise emission of ships. Their experiments proved the efficiency of this model in controlling emission levels. To solve the general fuel consumption rate functions more efficiently, Wang et al. (2013) further put forward a static and a dynamic quadratic outer approximation approaches. Du et al. (2015) also focused on BAPs in tidal ports from the perspective of emissions from vessel activities. Based on daytime preference that involves energy saving, Hu (2015) proposed a bi-objective model on BAPs in order to minimize the workloads at nights and the delayed workloads at the terminal operations. Venturini et al. (2017) addressed BAPs in green ports and considered the speed-control factor and the emission control factor. Hou (2017) explored a dynamic BAP based on the application of shore power. The target of this research is to minimize the total fuel cost, penalty cost and emissions. The quay crane scheduling and allocation problems are also important in quayside operations. Talavera et al. (2016) reported that the emissions from quay cranes affect bay allocation and quay crane workload distribution, which should be focused on for minimizing the emissions in terminals. With regard to tides at ports and fuel consumption of vessels, Yu et al. (2017b) addressed a quay crane scheduling problem by presenting a mixed-integer nonlinear programming model. Liu and Ge (2018) developed a convex mathematical model of a quay crane assignment problem for minimizing CO₂ emissions when unloading containers from quay cranes to automatic guided vehicles, based on the queueing theory. Some recent work integrates the problem on quay crane and BAP. Hu et al. (2014) proposed a multi-objective mathematical model for the integrated problem of berth and quay crane allocation by taking into account of fuel consumption and emissions. He (2016) investigated a berth allocation and quay crane assignment problem for trading off energy and time saving with the aim of minimizing the total energy consumption and departure delay of all ships. Considering a unitary carbon emission taxation rate and a piecewise carbon emission taxation rate, Wang et al. (2018) developed two models on the joint problem of berth allocation and quay crane assignment, which were then eased by some equivalent and relaxed models.

In yard side operations, the topic on yard crane combining with the concept of green ports is a typical research area recently. Rizaldi et al. (2015) presented three methods, including a market-based method, a zonal 1-1 method and a zonal 1-2 method, to coordinate a special type of yard cranes, i.e., Rubber-Tyred Gantry cranes (RTG). The efficiency of these coordination methods is evaluated by estimating the utilization of the cranes, the fuel consumption values of the cranes, and the waiting time of trucks. Different from the traditional approaches, He et al. (2015a) studied a yard crane scheduling problem considering energy consumption. A mixed integer programming model with soft time windows was built for minimizing the total energy consumption of yard cranes and the total delay of tasks. A simulation is designed for assessing the solutions and an optimization algorithm, integrating genetic algorithm (GA) and particle swarm optimization (PSO), is developed for searching the solution space. He et al. (2015b) addressed a joint scheduling problem of three types of handling equipment at container terminals, i.e., quay cranes, internal trucks and yard cranes, with the purpose of minimizing the total energy consumption of tasks and the total departure delay of ships. Moreover, the same integrated algorithm of GA and PSO is employed in this paper. Peng et al. (2016) focused on electric rubber tire container gantry cranes and addressed a yard crane allocation problem with limited resources considering the carbon emissions. A general model on the energy replacement problem (from diesel to electricity) is developed combining an allocation resource model and a simulation model. From the low carbon perspective, Sha et al. (2017) formulated a model related to energy consumption of yard cranes to optimize yard cranes scheduling at container terminals. In addition, an optimization of truck scheduling in yards is important in this field and widely studied (Bish et al., 2005; Lee et al., 2010). Yu et al. (2017a) proposed an optimization model and algorithm for the truck scheduling problem in yards in relation to CO₂ emissions. Kavakeb et al. (2015) introduced a green technology of emission reduction for equipment in yards and analyzed the influence of the application on European ports. To reduce trucks emissions in yards, automatic guided vehicle (AGV) is often applied. Thereafter, a greedy algorithm proposed by Chen et al. (1998) can be used to solve the problem.

3.2 Research on optimizing the operations management in green shipping network

In recent years, scholars from all over the world have conducted in-depth research on the management optimization of general shipping networks, and most have been reviewed by Meng et al. (2014). Agarwal and Ergun (2008) presented problems related to the optimization of liner service networks, including route design, ship capacity allocation, and cargo flow distribution. They addressed the problem by a mixed integer programming model based on the column generation-based heuristic algorithm and Benders decomposition-based heuristic algorithm. Jin et al. (2014) applied a tabu search algorithm to solve the mathematical model for the utilization of idle capacity in shipping networks in relation to vessel speed and amount of ships. The results of experiments show that the rate of idle ships and operating costs can be decreased by applying low-speed shipping. Scholars have also considered several emergent factors, such as cargo transshipments (Wang and Meng, 2012a), diversity of demand and competition among shipping alliances (Zhao, 2015), buyer preferences (Chen et al., 2017), distribution of benefits within shipping alliances (Agarwal and Ergun, 2010; Zheng et al., 2015), and speed optimization of vessels (Wang and Meng, 2012b; Psaraftis and Kontovas, 2014; Xia et al., 2015).

The research regarding the management of green shipping networks mainly focuses on the speed optimization of vessels. On the one hand, the speed optimization of vessels reduces fuel cost. Alvarez (2009) and Brouer et al. (2014) considered the optimal uniform speed setting on a single-route design of the liner network. Norstad et al. (2011) addressed the optimization problem of vessel speed in a single route by assuming that port anchorage is constrained by the time window. They then developed a set of divide-and-conquer algorithm based on recursive ideas to solve the problem. Xia et al. (2015) offered a novel perspective for shipping companies to optimize vessel speed by relating cargo weight

with fuel consumption. On the other hand, the speed optimization of vessels involves carbon oxide emissions, and some research results were reviewed by Psaraftis and Kontovas (2013). Lindstad et al. (2011) analyzed the impact of low-speed shipping on controlling the emissions of greenhouse gases. Yu and Wang (2015) optimized ship speed under different carbon emission control policies by trading off carbon emission reduction caused by speed reduction and change in carbon emissions caused by the amount of ships, and then established a speed optimization model based on different emission control policies. Zhu et al. (2016) established a fleet allocation optimization model considering the carbon emission trading mechanism for liner shipping companies and verified the findings by random experiments.

IMO has gradually established several ECAs. Due to the ECA policy, ships have to use low-sulfur fuel in ECAs, but the burden is on shipping companies. Doudnikoff and Lacoste (2014) argued that low-speed shipping can be applied to avoid extra fuel cost in ECAs. Chen et al. (2018) focused on the influence of ECA on the choice of shipping route, which suggests that many ships can reroute to save on fuel cost. In certain conditions, this phenomenon will indirectly affect the surrounding area of ECA. Therefore, the implementation of the ECA policy needs to be supported by many other aspects. Under the ECA policy, the related government department needs to control the emissions, whereas shipping companies need to control operating costs; the joint role renders the optimization problem of shipping network management under emission control policies a central topic for research. However, articles on ECA are generally lacking. Lv and Mao (2017) addressed the joint optimization problem of selecting ship types and corresponding amount and speed under the ECA policy. Fagerholt et al. (2015) developed a mixed integer programming model to solve the joint optimization problem of ship and route selection near the ECA based on the linear approximation of the fuel consumption function. The numerical experiments showed that ships will likely take the long route outside ECA to reduce navigation distance and then minimize fuel consumption within ECAs. In addition, the ship will sail slower within ECAs and faster outside ECAs to keep the total sailing time constant, thus reducing fuel consumption within ECAs. Fagerholt and Psaraftis (2015) proposed a mathematical formulation for both speed optimization problems (i.e., within and outside ECAs) under the emission control policy for ECA by introducing the concept of ECA refraction problem, in which optimal speeds and crossover points through the ECA boundary can be determined. Gu and Wallace (2017) investigated the influence of scrubbers on ECA as a novel perspective, and they found that the sailing pattern of ships is an important factor and the effect of scrubbers is closely related to port call density.

3.3 Research on emission control measures and related policies in green shipping

In view of the increasingly prominent role of the maritime transport industry in international trade, pollutant emissions caused by the increasing number of shipping vessels in recent years have been the focus of the international community, maritime authorities, industry associations, and the academia. In 2011–2014, IMO added technical and operational measures for shipping emissions to Annex VI of the MARPOL in the form of amendments. Thus far, in the IMO framework, three aspects have been considered to solve the problem of pollutant emissions in the shipping industry, and they involve technical, operational, and market-based measures (MBMs).

Pollutants such as CO₂, SO_x, and NO_x are emitted during shipping. To improve fuel efficiency and reduce fuel consumption, a more advanced technology needs to be applied to the shipping equipment. Among the technical measures, IMO has introduced the new energy efficiency design index (EEDI), which aims to provide a fair basis to compare ships of different types and sizes and encourage the development of efficient shipping. The index refers to environmental cost (contaminant emissions) generated by social benefits (freight volume) created per unit of shipping (Li et al., 2015). Ančić and

Šestan (2015) have observed that emission reduction factors can determine the actual EEDI of ships in the dry bulk market, and they provided a specific emission reduction strategy based on this observation. Cheng and Li (2012) proposed a new concept based on the EEDI; used the Fairplay database to calculate for the tanker, bulk carrier, and container ship; and compared the results via the EEDI benchmark method. However, this approach does not consider the impact of ship speed. Nonetheless, the accuracy of the EEDI benchmark method was verified on the basis of analytical results.

The technical measures for pollutant emission reduction mainly focus on newly built ships. In the IMO framework, such measures are mandatory to some extent, but they do not restrict most of the existing operating ships. Therefore, the IMO proposed the ship energy efficiency management plan (SEEMP), which is mainly focused on existing operating ships. In other words, the operational measures for the shipping industry to reduce emissions have been considered, but the implementation is not mandatory. During operation, a ship's energy efficiency management plan is reflected by the energy efficiency operational indicator (EEOI), which is directly related to fuel consumption.

Acomi and Acomi (2014) developed a method to calculate EEOI, and they analyzed the influence of different types of fuels in relation to EEOI value in full load and no-load conditions based on system analysis. Lu et al. (2015) established a semi-positive operation performance prediction model to support the operators in selecting optimal navigation speed according to ship characteristics. They applied the model for analyzing fuel consumption in different conditions. Sun et al. (2013) empirically analyzed the operational efficiency of inland vessels, and they found that navigation environments can remarkably affect the operational efficiency of inland vessels based on the calculated energy efficiency index of ships in calm water and real navigation conditions.

The MBMs in the emission reduction of shipping focus on economic and market incentives to encourage companies to adopt the most economical approach for reducing emissions and minimizing costs while meeting emission reduction targets. Thus, MBMs have been regarded one of the main measures for controlling carbon oxide emissions in the international maritime industry. However, the emission reduction principle needs to reconcile the two principles of international law (i.e., “common but differentiated responsibilities” and “no more preferential treatment”), but a plan acceptable to both developed and developing countries has yet to be proposed. Heitmann and Khalilian (2011), who discussed the influence of various proposals from the UN Framework Convention on Climate Change (UNFCCC), found that no existing proposal can effectively and fairly solve the emission problems. Lee et al. (2013) analyzed the economic impact of carbon tax on international container transportation. The results showed that the introduction of seaborne carbon tax in international container transportation will not lead to significant global economic changes in low-carbon tax condition; rather, the loss of GDP in China is the greatest and this introduction will affect long-distance container routes in high-carbon tax conditions. Wang et al. (2015b) discussed two sets of measures in the emissions trading system (ETS), namely, open ETS and shipping industry ETS. An in-depth research was conducted to analyze the influence of these two ETS measures in controlling emissions. Shi (2016) discussed the current seven emission reduction measures of greenhouse gas fund, port state taxation, energy efficiency incentive, ship energy efficiency and credit transactions, international shipping global CO₂ emission trading system, trade development penalties, and tax refund mechanism as an international shipping marketization tool. A comparison of the scope of the seven measures showed that greenhouse gas reduction is acceptable to many countries, and it has thus been recommended for implementation in 2016. Meanwhile, domestic scholars have focused on the policy interpretation of MBMs, which generally suggest the neglect of quantitative research. Zhang and Zhang (2008) analyzed the design elements, possible main problems, and development trends of the international shipping carbon

emission trading mechanism. On the basis of the results, they proposed for China to urgently focus on the establishment of a comprehensive database on ship information to determine the influence of emission trading mechanism on China's shipping industry and the investigation of the political and economic impact of international shipping emission trading mechanisms. Li (2012) analyzed the recent emission reduction situation in China and found that problems are mainly associated with weak foundation, inadequate management mechanism, and insufficient technology accumulation; subsequently, the potential market for low carbon development was proposed.

In addition to the aforementioned strategies for shipping companies to reduce emissions, many countries have also set up ECAs around their ports to limit emissions in controlled areas. Panagakos et al. (2014) focused on the strategy of opening a sulfur ECA in the Mediterranean. They compared the cost and level of emissions from both road and waterway transportation by applying the logit model, and they found that this strategy will force 5.2% of transportation transfer into road transportation. Fagerholt et al. (2015) developed a route–speed model to minimize operating costs and meet ECA requirements. They found that shipping companies will choose to avoid ECAs and speed up outside ECAs to cover lost time cost. By contrast, Adland et al. (2017) applied the automatic identification system (AIS) to obtain data from more than 7000 ships that sail through ECAs in the Northern Sea, and they found that the ECA policy does not affect the speed of visiting ships.

Many scholars have conducted research on the existing emission control policies issued by IMO or government maritime departments for shipping companies. Zhao et al. (2015) proposed an optimization model for container terminals considering transportation, port calls, and discharge costs and limiting capacity of ports. Jia et al. (2015) established a system involving 17 indicators for the development of green shipping, and identified the significance of each indicator. Wang et al. (2016) proposed a model based on price compensation and found that this strategy will benefit ports and shipping companies and simultaneously reduce emission.

To further reduce at-berth emissions, especially NO_x and PM, governments currently promote the use of shore-side power (SP), which enables ships at berth to use electricity from national grids to power onboard electrical systems, such as lighting, ventilation, communication, and cargo pumps, while auxiliary engines are turned off. Shore power can considerably reduce air pollutant emissions, which can cause health problems, climate change, and environmental damage. Using shore power can reduce emissions of CO_2 by up to 85% (Hall, 2010), SO_2 by 88%, NO_x by 94%, and PM by 95% (Wang et al., 2015a). Furthermore, an international standard on SP is being developed to ensure worldwide compatibility between ports and vessels (IMO, 2017). Most shore power-related studies focus on cost–benefit analysis, i.e., whether a port should install SP infrastructures (a health benefit from reducing emissions versus the installation cost of SP infrastructure), by assuming a fixed percentage of SP utilization. Ballini and Bozzo (2015) assumed 60% of all cruise vessels visiting Copenhagen used shore power, and their calculated results show that the total capital cost of establishing SP infrastructures in Copenhagen will be compensated by health benefits in 12–13 years. Zis et al. (2016) analyzed the payback period for ships retrofitted with SP equipment and found that payback time depends on the price of fuel and electricity and the time spent at berth. The promotion of SP requires both ports and shipping lines to invest in infrastructure/facilities considering one another's decision. However, limited studies account for this network effect. A previous research (Port of Long Beach, 2004) found that vessels who call in more than six times in a year, also called “frequent flyers,” accounted for more than 40% of all vessel calls. Once SP infrastructures are installed, these frequent flyers will also be retrofitted to accommodate the SP infrastructure. Wang et al. (2015a) assumed that 40% of ships visiting the port of Shenzhen come from ports in Europe and North America and are

already equipped with SP equipment, and they evaluated potential emission reduction if the port installs an SP infrastructure. Vaishnav et al. (2016) used historical vessel call data and identified combinations of vessels and berths at US ports that can be switched to shore power to yield the largest gains for society. They assumed that port operators and ship owners act in a socially optimal manner. The abovementioned studies incorporate one-stage interaction between ports and shipping lines. However, in practice, ports and shipping lines interact repeatedly in a “chicken and egg” manner (Winkel et al., 2016). In other words, as more ports build shore power infrastructure, ships with SP equipment will have more opportunities to use SP, thus reducing the cost for shipping companies; as a result, more ships will be retrofitted, and even more ports will install SP infrastructure (Wang et al., 2015a).

4 Discussions on literature

This study has reviewed more than 80 related papers to provide a comprehensive overview of green port and maritime shipping network operations management. The target of the paper is to summarize the existing literature and identify some future research directions. Three related research areas are analyzed in Sections 3.1, 3.2 and 3.3. In the first research area, we pay attention to the green ports regarding quayside and yard side operations. There are numerous studies investigating port operations management, but the research combining with the concept of “green” is far from enough. For example, storage location allocation is a central problem in yard side operations and widely studied (Murty et al., 2005; Kozan and Preston, 2006), while we lack the research integrating this central issue and energy saving or emission reduction. In the second research area, the joint problem of speed optimization and fuel cost or carbon oxide emissions as well as some studies on ECAs is reviewed and reported. Some extant papers reveal that if the measure of fuel switching is chosen for obeying ECA regulations, there usually exist two schemes to minimize fuel cost, i.e., avoiding ECAs, and sailing slower within ECAs and faster outside ECAs. In the last research area, we analyze emission control measures from perspectives of technical measure (i.e., the introduction of EEDI), operational measure (the proposal of SEEMP), and MBM that focuses on economic and market incentives for reducing cost and emission. A large number of existing works for carbon emission reduction in shipping are discussed in our paper, and it is likely to reduce carbon dioxide emissions with current technologies as reported by Bouman et al. (2017). Moreover, we also investigate the papers on the emission control policies and especially focus on the cost-benefit analysis of SP infrastructures.

In sum, four conclusions can be drawn from the review of aforementioned articles.

(i) Although there are many articles regarding the operations management of ports, the traditional decision model has to be improved and adjusted to adapt to the concept of green ports. Scholars need to consider the concept from a different perspective, such as the analysis of emission mechanism in port operation, the optimization of operation in ports considering emission control, and the optimization of operations management considering emission control. They need to expand research from a different perspective, redefine the existing scheduling problem of resource in ports, try to propose the evaluation and regulation method to control emission, and investigate the joint optimization problem from a more extensive view to solve the problems ports operators are facing in the development of green ports.

(ii) Optimization in liner operation regarding emission control is a new research topic. For example, the speed and route of ships need to be reconstructed due to the set of sulfur emission control area, or several elements such as the cost of heavy-sulfur and low-sulfur fuel, fuel consumption, the location, size, and shape of the control area need to be considered to save the fuel consumption cost. Specific models and algorithms need to be proposed to meet the need of green ports and contribute to economic and environmental development.

(iii) Considering emission control policies, the fuel cost, the fleet deployment, and the schedule design will be affected by the installation of the scrubber and shore power equipment. Under the

emission control policy, port operators need to decide whether they need to adopt the new technology for emission control, equip ships with the scrubber, and upgrade the ships for shore power transformation. Little research is available with regard to the adoption of new technology on shipping emission reduction, especially in quantitative decision theory and methods.

(iv) Few systematic analysis is present for emission control policies. For example, the enforcement of EEDI will continuously affect the operating mechanism. Similarly, the implementation of EEOI and MBMs will promote the relationship between policies. In addition, several articles regarding green shipping based on the quantitative decision method treat the emission control policies as the given condition, which means they analyze the operating strategy under certain policy and they fail to conduct in-depth research for current emission control policies and verify the rationality of emission grading policies. Emission control policies need to be further explored.

5 Potential topics for future studies

Based on the aforementioned conclusions, problems in the field of green ports and greening shipping network are proposed in this paper. These potential topics mainly focus on the short-term tactical level and long-term strategic level of operation management problem, from the perspective of sustainability, based on the operation research. It involves four research areas: (i) dynamic evaluation of port operations based on emission grading policies, (ii) optimization of port operations under emission control policies, (iii) optimization of potentially adopted green port and shipping technologies under emission grading policies and emission control policies, and (iv) analysis and optimization of emission control, emission grading, and other subsidy policies. The potential topics are proposed from several different dimensions: decision subject, decision-making level, and decision object. The framework of potential topics is shown in Table 1.

Table 1 Framework of potential topics

	Decision subject	Decision-making level	Decision object	Research topics
Enterprise	Ports	Short-term tactical level	Points in shipping network	Dynamic evaluation of port operations based on emission grading policies
	Shipping companies		Lines in shipping network	Optimization of port operations under emission control policies
	Port and shipping companies	Long-term strategic level	Shipping network	Optimization of potentially adopted green port and shipping technologies under emission grading policies and emission control policies
Government	Maritime management department, environmental protection department, and so on	Macro-policy level	Shipping network	Analysis and optimization of emission control, emission grading, and other subsidy policies

Future work could also focus on automated equipment at port, such as automated mooring systems, automated guided vehicle and automated stacking cranes. Some scholars have explored this area for optimizing operation performance (Pjevčević et al., 2011; Kavakeb et al., 2015), while there is still a lack of studies on automated equipment. For example, it is interesting to explore the problem on improving efficiency of automated equipment with some uncertain factors as uncertainty is a critical concern in port operations management. In addition, for saving energy and reducing emissions, the

research associated with new green shipping technologies is needed, such as battery, bioenergy, and nuclear energy.

6 Summary

In this paper, the research results on ports and shipping network and emission control are discussed together the construction of the optimization theory system for green ports and shipping network management. Then, the potential topics for green port and shipping network optimization management are proposed. This paper accords with the concept of sustainability, as it involves meeting targets on emission reduction in shipping activities, improving the service level of shipping companies, and controlling operating cost. The construction of the optimization theory system of green port and shipping network management not only benefits the development of management science, system science, and decision optimization theory, but it also forwards the conceptualization of related models for shipping companies to balance between cost savings and emission control. New tools for decision making on the development of green ports can be developed; decision-making processes for government regulation departments can be enhanced; and scientific evidence for the adoption of new technologies regarding emission reduction in shipping companies can be supported. Moreover, shipping activities can be optimized while meeting the emission control requirement. The potential topics proposed in this paper are vital in decreasing the emission of pollutants from shipping activities, promoting low-carbon economy, protecting safety of lives, and improving the sustainability of global economic society.

Acknowledgment

This paper is supported by the key project of NSFC (NO. 71831008). The authors appreciate the support of all the team members in this key project.

Conflict of interest statement

We declare that we have no conflict of interest.

References

- Acomi N, Acomi O (2014). The influence of different types of fuel over the energy efficiency operational index. *Energy Procedia*, 59: 243-248
- Adland R, Fonnes G, Jia H, Lampe O D, Strandenes S P (2017). The impact of regional environmental regulations on empirical vessel speeds. *Transportation Research Part D*, 53: 37-49
- Agarwal R, Ergun O (2008). Ship scheduling and network design for cargo routing in liner shipping. *Transportation Science*, 42(2): 175-196
- Agarwal R, Ergun O (2010). Network design and allocation mechanisms for carrier alliances in liner shipping. *Operations Research*, 58(6): 1726-1742
- Alvarez J F (2009). Joint routing and deployment of a fleet of container vessels. *Maritime Economics & Logistics*, 11(2): 186-208
- Ančić I, Šestan A (2015). Influence of the required EEDI reduction factor on the CO₂ emission from bulk carriers. *Energy Policy*, 84: 107-116
- Ballini F, Bozzo R (2015). Air pollution from ships in ports: The socio-economic benefit of cold-ironing technology. *Research in Transportation Business & Management*, 17: 92-98
- Bish E K, Chen F Y, Leong Y T, Nelson B L, Ng J W C, Simchi-levi D (2005). Dispatching vehicles in a mega container terminal. *OR Spectrum*, 27(4): 491-506
- Bouman E A, Lindstad E, Rialland A I, Strømman A H (2017). State-of-the-art technologies, measures, and potential for reducing GHG emissions from shipping – A review. *Transportation Research Part D*, 52: 408-421
- Brouer B D, Alvarez J F, Plum C E M, Pisinger D, Sigurd M M (2014). A base integer programming model and benchmark suite for liner-shipping network design. *Transportation Science*, 48(2): 281-312
- Buhaug Ø, Corbett J, Endresen Ø, Eyring V, Faber J, Hanayama S, Lee D, Lindstad H, Markowska A, Mjelde A (2009). *Second IMO GHG Study*. London: International Maritime Organization (IMO)
- Chen K, Xu P, Yang Z (2017). Optimization model of liner transportation system considering cargo owner's choice inertia. *Journal of Management Sciences in China*, 20(7): 104-114
- Chen L, Yip T L, Mou J (2018). Provision of emission control area and the impact on shipping route choice and ship emissions. *Transportation Research Part D*, 58: 280-291
- Chen Y, Leong Y T, Ng J W C, Demir E K, Nelson B L, Simchi-Levi D (1998). Dispatching Automated Guided Vehicles in a Mega Container Terminal. *INFORMS Meeting, Montreal*

- Cheng H, Li B (2012). A comparative study of EEDI criterion methods. *Shipbuilding of China*, 53: 103-109
- Cordeau J F, Laporte G, Legato P, Moccia L (2005). Models and tabu search heuristics for the berth allocation problem. *Transportation Science*, 39(4): 526-538
- Davarzani H, Fahimnia B, Bell M, Sarkis J (2016). Greening ports and maritime logistics: A review. *Transportation Research Part D*, 48: 473-487
- Doudnikoff M, Lacoste R (2014). Effect of a speed reduction of containerships in response to higher energy costs in sulphur emission control areas. *Transportation Research Part D*, 28: 51-61
- Du Y, Chen Q, Lam J S L (2015). Modeling the impacts of tides and the virtual arrival policy in berth allocation. *Transportation Science*, 49(4): 939-956
- Du Y, Chen Q, Quan X, Long L, Fung R Y K (2011). Berth allocation considering fuel consumption and vessel emissions. *Transportation Research Part E*, 47: 1021-1037
- Fagerholt K, Gausel N T, Rakke J G, Psaraftis H N (2015). Maritime routing and speed optimization with emission control areas. *Transportation Research Part C*, 52: 57-73
- Fagerholt K, Psaraftis H N (2015). On two speed optimization problems for ships that sail in and out of emission control areas. *Transportation Research Part D: Transport and Environment*, 39: 56-64
- Fransoo J C, Lee C Y (2013). The critical role of ocean container transport in global supply chain performance. *Production and Operations Management*, 22(2): 253-268
- Giallombardo G, Moccia L, Salani M, Vacca I (2010). Modeling and solving the tactical berth allocation problem. *Transportation Research Part B*, 44(2): 232-245
- Gu Y, Wallace S W (2017). Scrubber: A potentially overestimated compliance method for the emission control areas: The importance of involving a ships sailing pattern in the evaluation. *Transportation Research Part D: Transport and Environment*, 55: 51-66
- Hall W J (2010). Assessment of CO₂ and priority pollutant reduction by installation of shoreside power. *Resources, Conservation and Recycling*, 54(7): 462-467
- He J (2016). Berth allocation and quay crane assignment in a container terminal for the trade-off between time-saving and energy-saving. *Advanced Engineering Informatics*, 30(3): 390-405
- He J, Huang Y, Yan W (2015a). Yard crane scheduling in a container terminal for the trade-off between efficiency and energy consumption. *Advanced Engineering Informatics*, 29(1): 59-75
- He J, Huang Y, Yan W, Wang S (2015b). Integrated internal truck, yard crane and quay crane scheduling in a container terminal considering energy consumption. *Expert Systems with Applications*, 42(5): 2464-2487
- Heitmann N, Khalilian S (2011). Accounting for carbon dioxide emissions from international shipping: Burden sharing under different UNFCCC allocation options and regime scenarios. *Marine Policy*, 35: 682-691
- Hou J (2017). Dynamic berth allocation problem with two types of shore power for containership based on rolling horizon strategy. In: 2017 2nd IEEE International Conference on Intelligent Transportation Engineering (ICITE). Singapore, 144-149
- Hu Q M, Hu Z H, Du Y (2014). Berth and quay-crane allocation problem considering fuel consumption and emissions from vessels. *Computers & Industrial Engineering*, 70: 1-10
- Hu Z (2015). Multi-objective genetic algorithm for berth allocation problem considering daytime preference. *Computers & Industrial Engineering*, 89: 2-14
- Imai S, Nishimura E, Papadimitriou S (2001). The dynamic berth allocation problem for a container port. *Transportation Research Part B*, 35(4): 401-417
- IMO (2008). Revised MARPOL Annex VI: Regulations for the prevention of air pollution from ships and NO_x technical code. London: IMO Marine Environmental Protection Committee (MEPC)
- IMO (2017). International Maritime Organization. <http://www.imo.org/en/Pages/Default.aspx>, 2017-10-09
- Jia P, Govindan K, Kannan D (2015). Identification and evaluation of influential criteria for the selection of an environmental shipping carrier using DEMATEL: A case from India. *International Journal of Shipping & Transport Logistics*, 7: 719-741
- Jin Z, Li N, Han J (2014). Fleet deployment optimization of container liner routes under the unbalance of supply and demand. *Journal of Dalian Maritime University*, 35(1): 21-28
- Kavakeb S, Trung T N, McGinley K (2015). Green vehicle technology to enhance the performance of a European port: A simulation model with a cost-benefit approach. *Transportation Research Part C*, 60: 169-188
- Kozan E, Preston P (2006). Mathematical modeling of container transfers and storage locations at seaport terminals. *OR Spectrum*, 28(4): 519-537
- Lee C Y, Song D P (2017). Ocean container transport in global supply chains: Overview and research opportunities. *Transportation Research Part B*, 95: 442-474
- Lee L H, Chew E P, Tan K C, Wang Y (2010). Vehicle dispatching algorithm for container transshipment hubs. *OR Spectrum*, 32(3): 663-685
- Lee T, Chang Y, Lee P (2013). Economy-wide impact analysis of a carbon tax on international container shipping. *Transportation Research Part A*, 58: 87-102
- Li B (2012). The status of energy saving and emission reduction and the methods of low carbon development in shipping industry. *Journal of Engineering Studies*, 4: 260-269
- Li H, Zhang H, Wu G (2015). Analysis of EEDI influencing factors of ships and measures. *China Water Transport*, 15: 68-69
- Lim A (1998). The berth planning problem. *Operations Research Letters*, 22(2-3): 105-110
- Lindstad H, Asbjørnslett B E, Stromman A H (2011). Reductions in greenhouse gas emissions and cost by shipping at lower speeds. *Energy Policy*, 39: 3456-3464
- Liu D, Ge Y E (2018). Modeling assignment of quay cranes using queueing theory for minimizing CO₂ emission at a container terminal. *Transportation Research Part D: Transport and Environment*, 61: 140-151
- Lu R, Turan O, Boulougouris E, Banks C, Incecik A (2015). A semi-empirical ship operational performance prediction model for voyage optimization towards energy efficient shipping. *Ocean Engineering*, 110: 18-28

- Lv J, Mao H (2017). An optimization model of liner ship fleet deployment under sulfur emission control area and carbon emission restriction. *Journal of Dalian Maritime University*, 43(1): 101-105
- Meng Q, Wang S, Andersson H, Thun K (2014). Containership routing and scheduling in liner shipping: Overview and future research directions. *Transportation Science*, 48(2): 265-280
- Murty K G, Liu J, Wan Y, Linn R (2005). A decision support system for operations in a container terminal. *Decision Support Systems*, 39(3): 309-332
- Norstad I, Fagerholt K, Laporte G (2011). Tramp ship routing and scheduling with speed optimization. *Transportation Research Part C*, 19: 853-865
- Panagakos G P, Stamatopoulou E V, Psaraftis H N (2014). The possible designation of the Mediterranean Sea as a SECA: A case study. *Transportation Research Part D*, 28: 74-90
- Peng Y, Wang W, Song X, Zhang Q (2016). Optimal allocation of resources for yard crane network management to minimize carbon dioxide emissions. *Journal of Cleaner Production*, 131: 649-658
- Pjevčević D, Vladislavljević I, Vukadinović K, Teodorović D (2011). Application of DEA to the analysis of AGV fleet operations in a port container terminal. *Procedia-Social and Behavioral Sciences*, 20: 816-825
- Port of Long Beach (2004). Cold ironing cost effectiveness. <http://www.lbreport.com/port/coldiron.pdf>, 2017-10-12
- Psaraftis H N, Kontovas C A (2013). Speed models for energy-efficient maritime transportation: A taxonomy and survey. *Transportation Research Part C*, 26: 331-351
- Psaraftis H N, Kontovas C A (2014). Ship speed optimization: Concept, models and combined speed-routing scenarios. *Transportation Research Part C*, 44: 52-69
- Rizaldi A, Wasesa M, Rahman M N (2015). Yard cranes coordination schemes for automated container terminals: an agent-based approach. *Procedia Manufacturing*, 4: 124-132
- Sha M, Zhang T, Lan Y, Zhou X, Qin T, Yu, D, Chen K (2017). Scheduling optimization of yard cranes with minimal energy consumption at container terminals. *Computers & Industrial Engineering*, 113: 704-713
- Shi Y (2016). Reducing greenhouse gas emissions from international shipping: Is it time to consider market-based measures. *Marine Policy*, 64: 123-134
- Sun X, Yan X, Wu B, Song X (2013). Analysis of the operational energy efficiency for inland river ships. *Transportation Research Part D*, 22: 34-39
- Talavera A M, Barron J G G, Passamani C M T C (2016). Optimization of vessel and quay crane emissions during the hoteling phase. In: 2016 7th International Conference on Information, Intelligence, Systems & Applications (IISA). Chalkidiki, Greece: IEEE, 1-10
- UNCTAD (2011). Review of Maritime Transport 2011. United Nations, New York and Geneva
- UNCTAD (2015). Review of Maritime Transport 2015. United Nations, New York and Geneva
- Vaishnav P, Fischbeck P S, Morgan M G, Corbett J J (2016). Shore power for vessels calling at US ports: Benefits and costs. *Environmental Science & Technology*, 50(3): 1102-1110
- Venturini G, Iris C, Kontovas C A, Larsen A (2017). Multi-port berth allocation problem with speed optimization and emission considerations. *Transportation Research Part D*, 54: 142-159
- Wang F, Huang J, Liu Z (2017). Port management and operations: Emerging research hotspots and development. *Journal of Management Sciences in China*, 20(5): 111-126
- Wang F, Lim A (2007). A stochastic beam search for the berth allocation problem. *Decision Support Systems*, 42(4): 2186-2196
- Wang H, Mao X, Rutherford D (2015a). Costs and benefits of shore power at the Port of Shenzhen. *The International Council on Clean Transportation*
- Wang K, Fu X, Luo M (2015b). Modeling the impacts of alternative emission trading schemes on international shipping. *Transportation Research Part A*, 77: 35-49
- Wang S, Meng Q (2012a). Liner ship fleet deployment with container transshipment operations. *Transportation Research Part E*, 48(2): 470-484
- Wang S, Meng Q (2012b). Sailing speed optimization for container ships in a liner shipping network. *Transportation Research Part E*, 48: 701-714
- Wang S, Meng Q, Liu Z (2013). A note on "Berth allocation considering fuel consumption and vessel emissions". *Transportation Research Part E: Logistics and Transportation Review*, 49(1): 48-54
- Wang T, Lu L, Wang X (2016). Cooperation mode of port and shipping companies with the introduction of price compensation mechanism. *Resource Development & Market*, 32: 1409-1414
- Wang T, Wang X, Meng Q (2018). Joint berth allocation and quay crane assignment under different carbon taxation policies. *Transportation Research Part B*, 117: 18-36
- Winkel R, Weddige U, Johnsen D, Hoen V, Papaefthimiou S (2016). Shore side electricity in Europe: Potential and environmental benefits. *Energy Policy*, 88: 584-593
- Xia J, Li X, Ma H, Xu Z (2015). Joint planning of fleet deployment, speed optimization, and cargo allocation for liner shipping. *Transportation Science*, 49(4): 922-938
- Yu H, Ge Y E, Chen J (2017a). CO₂ emission evaluation of yard tractors during loading at container terminals. *Transportation Research Part D*, 53: 17-36
- Yu S, Wang C (2015). Ship speed optimization under different carbon emission control policies. *Journal of Dalian Maritime University*, 41(3): 45-50
- Yu S, Wang S, Zhen L (2017b). Quay crane scheduling problem with considering tidal impact and fuel consumption. *Flexible Services and Manufacturing Journal*, 29(3-4): 345-368
- Zhang S, Zhang S (2008). Trading mechanism framework for international maritime greenhouse gas emissions. *China Maritime Safety*, 9: 60-63
- Zhao Y (2015). Axle-spoke container shipping network design problem under competitive environment. *Chinese Journal of Management Science*, 23(7): 103-112
- Zhao Y, Duan H, Kuang H (2015). Axle-spoke container shipping network design considering CO₂ emissions. *Journal of Systems Engineering*, 30: 383-393
- Zhen L (2017). Optimization of Container Port Operation Management. Beijing: Science Press

- Zheng J, Gao Z, Yang D, Sun Z (2015). Network design and capacity exchange for liner alliances with fixed and variable container demands. *Transportation Science*, 49(4): 886-899
- Zhu M, Zhen H, Gan A (2016). Optimization of liner fleet deployment under carbon emission right trading. *Journal of Transportation Systems Engineering and Information Technology*, 16(1): 202-208
- Zis T, Angeloudis P, Bell M G H, Psaraftis H N (2016). Payback period for emissions abatement alternatives: Role of regulation and fuel prices. *Transportation Research Record*, 2549: 37–44